

Rec'd PCT/PTO

21 MAR 2002

**TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)  
CONCERNING A FILING UNDER 35 U.S.C. § 371**

449122025000

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

10/088688  
Not yet assigned

INTERNATIONAL APPLICATION NO.

PCT/DE00/03175

INTERNATIONAL FILING DATE

September 13, 2000

PRIORITY DATE CLAIMED

September 21, 1999

TITLE OF INVENTION

**METHOD AND ARRANGEMENT FOR COUPLING MESSAGES OF A CENTRAL CONTROL DEVICE  
WITH DECENTRALIZED COMMUNICATIONS DEVICES**

APPLICANT(S) FOR DO/EO/US

**Antonius EMMERINK et al.**

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:


1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below.
4. ☒ The US has been elected by the expiration of 19 months from the priority date (PCT Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
  - a. ☒ is attached hereto (required only if not communicated by the International Bureau).
  - b. ☒ has been communicated by the International Bureau.
  - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ An English language translation of the International Application under PCT Article 19 (35 U.S.C. 371(c)(2)).
  - a. ☒ is attached hereto.
  - b. ☐ has been previously submitted under 35 U.S.C. 154(d)(4).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).
  - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
  - b. ☐ have been communicated by the International Bureau.
  - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
  - d. ☐ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).


**Items 11. to 16. below concern document(s) or information included:**

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A FIRST preliminary amendment.
14. ☐ A SECOND or SUBSEQUENT preliminary amendment.
15. ☒ A substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
18. ☐ A second copy of the published international application under 35 U.S.C. 154(d)(4).
19. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
20. ☒ Other items: 1) Application Data Sheet; 2) Int'l Search Report; 3) IPER; 4) Return receipt postcard.

**CERTIFICATE OF HAND DELIVERY**

I hereby certify that this correspondence is being hand filed with the United States Patent and Trademark Office in Washington, D.C. on March 21, 2002.

  
Melissa Garton

APPLICATION NO (if known see 37 CFR 1.5) not yet assigned		INTERNATIONAL APPLICATION NO PCT/DE00/03175	ATTORNEY DOCKET NO. 449122025000
21. <input checked="" type="checkbox"/> The following fees are submitted: <b>BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(5)):</b> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO.....\$1,040.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO.....\$890.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO.....\$740.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provision of PCT Article 33(1)-(4) .....\$710.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) .....\$100.00			CALCULATIONS PTO USE ONLY
ENTER APPROPRIATE BASIC FEE AMOUNT =			\$890.00
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).			\$0
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	- 20 =		x \$18.00
Independent claims	- 3 =		x \$84.00
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$280.00
TOTAL OF ABOVE CALCULATIONS =			\$890.00
Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.			\$0
SUBTOTAL =			\$890.00
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).			+
TOTAL NATIONAL FEE =			\$890.00
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property			+
TOTAL FEES ENCLOSED =			\$930.00
			Amount to be refunded:
			charged: \$
a. <input checked="" type="checkbox"/> Please charge my <u>Deposit Account No. 03-1952</u> (referencing Docket No. 449122025000) in the amount of \$930.00 to cover the above fees. A duplicate copy of this sheet is enclosed. b. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees that may be required, or credit any overpayment to <u>Deposit Account No. 03-1952</u> (referencing Docket No. 449122025000).			
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.			
SEND ALL CORRESPONDENCE TO:			
Kevin R. Spivak Morrison & Foerster LLP 2000 Pennsylvania Avenue, N.W. Washington, D.C. 20006-1888			
 SIGNATURE			
Kevin R. Spivak Registration No. 43,148			
March 21, 2002			

I hereby certify that this correspondence is being hand filed with the United States Patent and Trademark Office in Washington, D.C. on March 21, 2002.

**Melissa Garton**

dc-308171

different communication protocols are used on the partial connection links, and a message is transmitted on the partial connection link directly using a respective communication protocol.

2. (Amended) The method as claimed in claim 1, in which, for the transformation from one communication protocol into another communication protocol, the message is initially unpacked from the protocol layers of one protocol and then packed into the protocol layers of the other protocol.

3. (Amended) The method as claimed in claim 1, in which an HDLC method is used during a first communication protocol on a lower protocol layer level and an Ethernet protocol or the ATM protocol is used during a second communication protocol on a lower layer.

4. (Amended) The method as claimed in claim 2, in which an Internet protocol is used on a network protocol layer.

5. (Amended) The method as claimed in claim 1, in which a control message is transmitted as the message.

6. (Amended) The method as claimed in claim 1, in which messages occur from a number of first decentralized devices, the messages are transmitted after passing through a first partial connection link in a second decentralized device in a bundled form and on one second partial connection link.

7. (Amended) The method as claimed in claim 6, in which groups of a number of first decentralized devices and second decentralized devices are administered.

8. (Amended) The method as claimed in claim 7, in which the messages from/to the second decentralized devices are initially sorted and then processed in the central control device.



9. (Amended) A system for coupling messages of a central control device with decentralized communication devices, comprising:
- a transport network for providing a communication connection;
  - a control network for controlling the setting-up and/or clearing-down of the communication connection;
  - a device to control the setting-up and/or clearing-down of a connection in the transport network by a control network, the device being spatially separate from the transport network;
  - at least one first decentralized communication device to receive and/or issuing a message;
  - at least one second decentralized communication device to collect and/or distributing messages;
  - a central control device to issue and receive messages;
  - at least one first communication connection between the first and second communication devices; and
  - a second communication connection between the second decentralized communication device and the central control device, the second communication connection being formed as an Internet or ATM network, and the first communication connection being formed as an HDLC-based connection.
10. (Amended) The system as claimed in claim 9, in which the second communication connection is formed as a coaxial cable or as an optical waveguide.
11. (Amended) The system as claimed in claim 9, in which the first communication connection is formed as a bus on a backplane.
12. (Amended) The system as claimed in claim 9, in which the second decentralized communication device is in operative connection with a converting device, which performs a protocol conversion between communication protocols on the first and second communication connections, for which purpose the messages are unpacked from protocol layers being used and re-packed.

13. (Amended) The system as claimed in claim 9, in which, for the case in which a number of second communication devices are connected via a number of second communication connections to the central control device, at least one device coordinates the messages, which sorts the messages arriving on the second communication connection, which is connected to a device to process the messages.

14. (Amended) The system as claimed in claim 9, in which the second communication connection is formed as an ATM network, the central control device has a first and a second central device, a converting device is present in the first central device, for the conversion between protocol layers of the Internet protocol via the ATM network to protocol layers of the Internet protocol via the Ethernet, and the first and second central devices are in connection with each other via an Ethernet connection.

15. (Amended) The system as claimed in claim 14, in which the second central device has the device for processing messages.

16. (Amended) The system as claimed in claim 14, in which the central control has a device to control a switching unit for the creation of time-slot multiplex connections, and the device is in operative connection with the device to process messages.

**In the Abstract:**

Please replace the Abstract with the substitute Abstract attached hereto.

## REMARKS


Amendments to the specification have been made and are submitted herewith in the attached Substitute Specification. A clean copy of the specification and a marked-up version showing the changes made are attached herewith. The claims and abstract have been amended in the attached Preliminary Amendment. All amendments have been made to place the application in proper U.S. format and to conform with proper grammatical and idiomatic English. None of the amendments herein are made for reasons related to patentability. No new matter has been added.

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached page is captioned "**Version with markings to show changes made**".

In the unlikely event that the transmittal letter is separated from this document and the Patent Office determines that an extension and/or other relief is required, applicant petitions for any required relief including extensions of time and authorizes the Commissioner to charge the cost of such petitions and/or other fees due in connection with the filing of this document to **Deposit Account No. 03-1952** referencing docket no. 449122025000. However, the Commissioner is not authorized to charge the cost of the issue fee to the Deposit Account.

Respectfully submitted,

Dated: March 21, 2002

  
Kevin R. Spivak  
Registration No. 43,148

Morrison & Foerster LLP  
2000 Pennsylvania Avenue, N.W.  
Washington, D.C. 20006-1888  
Telephone: (202) 887-6924  
Facsimile: (202) 263-8396

**VERSION WITH MARKINGS TO SHOW CHANGES MADE**

For the convenience of the Examiner, the changes made are shown below with deleted text in strikethrough and added text in underline.

**In the Claims:**

~~Patent claims~~ What is claimed is:

1. (Amended) A method for coupling messages of a central control device with decentralized communication devices, ~~having the following features comprising:~~
  - a) ~~a connection function for setting up and/or clearing down a communication connection for the transport of communication data~~ which is performed by at least one first functional unit of a communication network;
  - b) ~~a control function for controlling the connection function~~ which is performed by a second functional unit of the communication network; wherein
  - e) the first and second functional units are spatially separate from each other; ~~characterized in that~~
  - d) message traffic ~~takes place~~ occurs on at least two partial connection links (~~KV1, 1001~~);
  - e) different communication protocols are used on the partial connection links; and
  - f) ~~a respective message is transmitted on the partial connection link directly as such with~~ the using a respective communication protocol.
2. (Amended) The method as claimed in claim 1, in which, for the transformation from one ~~type of~~ communication protocol into another ~~type of~~ communication protocol, the message is initially unpacked from the protocol layers of one protocol and then packed into the protocol layers of the other protocol.
3. (Amended) The method as claimed in claim 1 ~~one of the preceding claims~~, in which an the HDLC method is used ~~in the case of~~ during a first communication protocol on a lower protocol layer level and an the Ethernet protocol or the ATM protocol is used ~~in the case of~~ during a second communication protocol on a lower layer.

4. (Amended) The method as claimed in claim 2 ~~or 3~~, in which ~~the~~ an Internet protocol is used on a network protocol layer.

5. (Amended) The method as claimed in claim 1 ~~one of the preceding claims~~, in which a control message is transmitted as the message.

6. (Amended) The method as claimed in ~~one of the preceding claims~~ claim 1, ~~in which,~~  
~~for the case~~ in which messages ~~take place~~ occur from a number of first decentralized devices (~~DZ12,...,DZ237~~), these messages are transmitted after passing through a first partial connection link (~~2012,..., 2237~~) in a second decentralized device (~~DZ1,...,DZ20~~) in a bundled form and on ~~only one~~ second partial connection link (~~1001,...,1020~~).

7. (Amended) The method as claimed in claim 6, in which groups of a number of first decentralized devices (~~DZ12,DZ15,DZ19~~) and second decentralized devices (~~DZ1~~) are administered.

8. (Amended) The method as claimed in claim 7, in which the messages from/to the second decentralized devices (~~DZ1,..., DZ10,DZ20~~) are initially sorted and then processed in the central control device (~~ZE2~~).

9. (Amended) ~~An arrangement~~ A system for coupling messages of a central control device with decentralized communication devices, comprising:

a) ~~which has~~ a transport network for providing a communication connection;  
b) ~~which has~~ a control network for controlling the setting-up and/or clearing-down of the communication connection;

c) ~~and which has means for controlling~~ a device to control the setting-up and/or clearing-down of a connection in the transport network by a control network, ~~these means~~ device being spatially separate from the transport network;

~~characterized by~~

d) at least one first decentralized communication device (~~DZ12,...,DZ237~~) for receiving to receive and/or issuing a message;

e) at least one second decentralized communication device (DZ1,...,DZ20) for collecting to collect and/or distributing messages;

f) a central control device (ZE2) for issuing to issue and receiving receive messages;

g) at least one first communication connection (2012,...,2237) between the first and second communication devices; and

a second communication connection (1001,...,1020) between the second decentralized communication device (DZ1,...,DZ20) and the central control device (ZE2), the second communication connection being formed as an Internet or ATM network, and the first communication connection being formed as an HDLC-based connection.

10. (Amended) The arrangement system as claimed in claim 9, in which the second communication connection (1001,...,1020) is formed as a coaxial cable or as an optical waveguide.

11. (Amended) The arrangement system as claimed in claim 9 ~~one of claims 9 or 10~~, in which the first communication connection (2012,...,2237) is formed as a bus on a backplane.

12. (Amended) The arrangement system as claimed in claim 9 ~~one of claims 9 to 11~~, in which the second decentralized communication device (DZ1,...,DZ20) is in operative connection with a converting device (HDL1, IP1), which performs a protocol conversion between communication protocols on the first and second communication connections, for which purpose the messages are ~~completely~~ unpacked from protocol layers being used and re-packed.

13. (Amended) The arrangement system as claimed in claim 9 ~~one of claims 9 to 12~~, in which, for the case in which a number of second communication devices (DZ1,...,DZ20) are connected via a number of second communication connections (1001,...,1020) to the central control device (ZE2), ~~there is at least one device there for coordination of~~ coordinates the messages (IP2, DCL2), which sorts the messages arriving on the second communication connection ~~or on the way there~~, which is connected to a device ~~for processing to process~~ the messages (DCL2).

14. (Amended) The arrangement system as claimed in claim 9 ~~one of claims 9 to 13~~, in which, ~~for the case in which~~ the second communication connection (~~1020,...,1001~~) is formed as an ATM network, the central control device (~~ZE2~~) has a first and a second central device (~~EZE2, ZZE2~~), a converting device (~~ZIP~~) ~~being~~ is present in the first central device (~~EZE2~~), for the conversion between protocol layers of the Internet protocol via the ATM network to protocol layers of the Internet protocol via the Ethernet (~~ZETH~~), and ~~in which~~ the first and second central devices (~~EZE2, ZZE2~~) are in connection with each other via an Ethernet connection (~~Z2020~~).

15. (Amended) The arrangement system as claimed in claim 14, in which the second central device (~~ZZE2~~) has the device for processing messages (~~DCL2~~).

16. (Amended) The arrangement system as claimed in claim 14 ~~one of claims 14 to 15~~, in which the central control (~~ZE2~~) has ~~means for controlling a device to control~~ a switching unit for the creation of time-slot multiplex connections, and ~~these means are~~ the device is in operative connection with the ~~means for processing device to process~~ messages (~~DCL2~~).

**In the Abstract:**

Please replace the Abstract with the substitute Abstract attached hereto.

## Abstract

[illegible]



Patent claims

1. A method for coupling messages of a central control device with decentralized communication devices having the following features:
  - a) a connection function for setting up and/or clearing down a communication connection for the transport of communication data is performed by at least one first functional unit of a communication network;
  - b) a control function for controlling the connection function is performed by a second functional unit of the communication network;
  - c) the first and second functional units are spatially separate from each other; characterized in that
  - d) message traffic takes place on at least two partial connection links (KV1, 1001);
  - e) different communication protocols are used on the partial connection links;
  - f) a respective message is transmitted on the partial connection link directly as such with the respective communication protocol.
2. The method as claimed in claim 1, in which, for the transformation from one type of communication protocol into another type of communication protocol, the message is initially unpacked from the protocol layers of one protocol and then packed into the protocol layers of the other protocol.
3. The method as claimed in one of the preceding claims, in which the HDLC method is used in the case of a first communication protocol on a lower protocol layer level and the Ethernet protocol or the ATM protocol is used in the case of a second communication protocol on a lower layer.

10088663-032102

4. The method as claimed in claim 2 or 3, in which the Internet protocol is used on a network protocol layer.
5. The method as claimed in one of the preceding claims, in which a control message is transmitted.
6. The method as claimed in one of the preceding claims, in which, for the case in which messages take place from a number of first decentralized devices (DZ12,...,DZ237), these are transmitted after passing through a first partial connection link (2012,..., 2237) in a second decentralized device (DZ1,...,DZ20) in a bundled form and on only one second partial connection link (1001,...,1020).
7. The method as claimed in claim 6, in which groups of a number of first decentralized devices (DZ12, DZ15, DZ19) and second decentralized devices (DZ1) are administered.
8. The method as claimed in claim 7, in which the messages from/to the second decentralized devices (DZ1,..., DZ10, DZ20) are initially sorted and then processed in the central control device (ZE2).
9. An arrangement for coupling messages of a central control device with decentralized communication devices,
  - a) which has a transport network for providing a communication connection,
  - b) which has a control network for controlling the setting-up and/or clearing-down of the communication connection,
  - c) and which has means for controlling the setting-up and/or clearing-down of a connection in the transport network by a control network, these means being spatially separate from the transport network,

characterized by

- d) at least one first decentralized communication device (DZ12,...,DZ237) for receiving and/or issuing a message,
  - e) at least one second decentralized communication device (DZ1,...,DZ20) for collecting and/or distributing messages,
  - f) a central control device (ZE2) for issuing and receiving messages,
  - g) at least one first communication connection (2012,...,2237) between the first and second communication devices,
  - h) a second communication connection (1001,...,1020) between the second decentralized communication device (DZ1,...,DZ20) and the central control device (ZE2), the second communication connection being formed as an Internet or ATM network, and the first communication connection being formed as an HDLC-based connection.
10. The arrangement as claimed in claim 9, in which the second communication connection (1001,...,1020) is formed as a coaxial cable or as an optical waveguide.
11. The arrangement as claimed in one of claims 9 or 10, in which the first communication connection (2012,...,2237) is formed as a bus on a backplane.
12. The arrangement as claimed in one of claims 9 to 11, in which the second decentralized communication device (DZ1,...,DZ20) is in operative connection with a converting device (HDLCl, IP1), which performs a protocol conversion between communication protocols on the first and second communication connections, for which purpose the

messages are completely unpacked from protocol layers being used and re-packed.

13. The arrangement as claimed in one of claims 9 to 12, in which, for the case in which a number of second communication devices (DZ1,...,DZ20) are connected via a number of second communication connections (1001,...,1020) to the central control device (ZE2), there is at least one device there for coordination of the messages (IP2, DCL2), which sorts [lacuna] arriving on the second communication connection or on the way there, which is connected to a device for processing the messages (DCL2).
14. The arrangement as claimed in one of claims 9 to 13, in which, for the case in which the second communication connection (1020,...,1001) is formed as an ATM network, the central control device (ZE2) has a first and a second central device (EZE2, ZZE2), a converting device (ZIP) being present in the first central device (EZE2), for the conversion between protocol layers of the Internet protocol via the ATM network to protocol layers of the Internet protocol via the Ethernet (ZETH), and in which the first and second central devices (EZE2, ZZE2) are in connection with each other via an Ethernet connection (Z2020).
15. The arrangement as claimed in claim 14, in which the second central device (ZZE2) has the device for processing messages (DCL2).
16. The arrangement as claimed in one of claims 14 to 15, in which the central control (ZE2) has means for controlling a switching unit for the creation of time-slot multiplex connections, and these means are in operative connection with the means for processing messages (DCL2).

METHOD AND ARRANGEMENT FOR COUPLING MESSAGES OF A  
CENTRAL CONTROL DEVICE WITH DECENTRALIZED COMMUNICATION  
DEVICES

This application claims priority to International Application No. PCT/DE00/03175 which was published in the German language on September 13, 2000.

The invention relates to a method and an arrangement for transporting messages, and in particular, to control messages, in a switching device, ~~in particular~~ such as a private branch exchange set up over a large area, in which a number of decentralized devices are controlled from a central device.

The requirements imposed on communication infrastructure installations, such as private branch exchanges for example, are constantly increasing. The cause for the increasing requirements with regard to the data transmission capacity of switching devices lies in the constantly increasing demand for voice, video and data communication and the consequence that networks of broader bands have to be used for establishing connections. The cause for greater flexibility with regard to the number of subscribers which can be connected to switching devices lies in the requirement for the infrastructure to keep pace technically with the flexibility of the business processes of the users of the communication device. This results in a great demand for flexible modularly expandable private branch exchanges.

Current devices are based on time-slot multiplexing connections between communication terminals which are

**THE UNIVERSITY OF CHICAGO**



5

## SUMMARY OF THE INVENTION

10

15

25

30

35

transmitted, whereby time advantages and higher data capacities in message transport are attainable.

Standardized communication protocols, set up in  
5 accordance with the OSI layer model (Open Systems  
Interconnect), are advantageously used, because  
standardized devices (chips, protocol stacks) for such  
protocols are available on the market, making it easily  
possible to meet the required increase in the  
10 transmission performance on a connection by using  
faster devices. Since ~~only~~ the messages themselves are  
transmitted on each partial connection link, in an  
optimum way ~~only~~ the volume of user data is transmitted  
and the data transmission structures can remain  
15 restricted to the necessary minimum.

In the case of a first protocol, the HDLC method is  
advantageously used on a lowermost layer level, because  
in this way the modules in the decentralized devices,  
20 which today already have an HDLC interface, can  
continue to be used. This HDLC method is  
advantageously combined with a second communication  
protocol, which on the lowermost layers either has an  
Ethernet protocol or transmits there in accordance with  
25 the ATM protocol. In this way it is possible to use  
networks that are established and available for long-  
distance transmission, it being possible as from layer  
3 to use the same protocol layers again for the network  
switching and transport, in spite of the different  
30 fundamentals. For this reason, mixed configurations of  
a wide variety of protocols and networks can also be  
set up without any technical development effort. The  
ATM transmission method is advantageously particularly  
suitable for use on a long-distance connection, because  
35 different transmission qualities can be set up on the  
connections, allowing defined time requirements to be  
met in the message traffic.



In a ~~development~~ one aspect of the ~~method described~~ invention, the Internet protocol is advantageously used on the network layer, because this Internet protocol is already available for a wide variety of transmission media, and consequently the same transport and network switching services can be used for the various transmission media.

In a ~~development~~ another aspect of the ~~method described~~ invention, control messages are advantageously transmitted, because in this case there are hard time requirements of the communication partners, according to the method describes no changes are required in the decentralized devices, transmission methods for control messages already exist for the HDLC method, because they have already been implemented in the case of current devices, and because a wide variety of networks can be used for the long-distance connections.

A ~~development of the method described is particularly~~ One embodiment of the invention is advantageously suitable for the coupling of a number of decentralized devices to a central control, because messages are collected coordinated and distributed in a decentralized manner and ~~just~~ have to be transmitted in a bundled manner on a line to the centre.

In the bundling, a number of messages can be advantageously packed into an IP packet and consequently the administrative effort of the protocols can be reduced. The ratio of user data to protocol data is better as a result, and consequently there is a reduced load on the network.

For the administration of a number of decentralized devices, it is advantageously possible to set up groups, for which messages are respectively collected and distributed, because in this way message collecting and distributing devices which can already be used for

10088655-032100

central devices of a known type can be used in decentralized devices.

For the case in which a number of groups of  
5 decentralized devices are administered, a sorting of  
the messages is advantageously carried out in the  
central control device before they are processed,  
because in this way a unique group-specific  
prioritizing and processing of the messages is made  
10 possible.

At least two types of connecting lines, on which  
different transmission protocols are implemented, are  
used particularly advantageously in an arrangement for  
15 coupling messages between a decentralized device and a  
central control device. For the exchange of messages  
in the local exchange area, HDLC-based protocols are  
advantageously used, because in this way already known  
and existing decentralized devices on the basis of the  
20 HDLC protocol with their critical time requirements in  
decentralized devices can continue to be used, and  
Internet connections or ATM connections, for which  
standardized products are established on the market,  
can be used for the long-distance connections of these  
25 decentralized devices to the central control device, so  
that, with regard to the transmission capacity, a broad  
spectrum can be easily covered by the acquisition of  
products generally available on the market.

30 Depending on the required transmission capacity and  
distance, various media, which are available for the  
most diverse networks, can be advantageously used for  
the long-distance connections. For this reason, in the  
case of a number of decentralized devices, mixed  
35 configurations comprising a wide variety of  
transmission media are also possible.

~~In a development of the arrangement described~~ another  
embodiment of the invention, first communication

connections advantageously take the form of a backplane bus, because in this way already existing modules can be taken over unchanged from conventional devices into new devices as decentralized devices. Likewise, this type of configuration requires less additional development effort for the development of decentralized devices.

The protocol conversion takes place particularly advantageously in the area of a decentralized device, because in this way the time-critical transmission in accordance with the HDLC method can be best ensured. Similarly, there is no need for additional devices which carry out a protocol conversion in the area of the private branch exchange. Moreover, converting devices arranged decentrally in this way are also able to be adapted exactly in their conversion capacity to the communication volume of the respective decentralized device, and consequently can be used particularly efficiently.

A special device, which sorts and distributes messages which are received by it from various second decentralized devices, or are to be sent to the latter, is provided particularly advantageously in the central control device for the administration of second communication connections. In this way, a defined message processing over a number of decentralized devices is ensured and the possibility that messages over a number of decentralized devices can also be processed in a prioritizable manner is advantageously ensured.

For the case in which the second communication connection is formed as an ATM network, the central control device is particularly advantageously divided into two units, of which only one ~~must have~~ has an ATM access, while the other may be connected to this unit via a current Ethernet connection. This type of

10088888 033402

configuration has the advantage that customary central control devices can continue to be used largely unchanged and do not have to be further developed for access to an ATM network. Furthermore, the ATM network can be used for the transmission both of control messages and for the transport of communication data between the terminals, only the Internet protocol having to be implemented on layer 3 of the communication protocol for the transmission of the control messages, and the transfer to the central control device to the Ethernet can also take place on this layer. It is consequently possible to dispense with Ethernet connections between the central control device and the decentralized communication devices. It should be noted here that the network topology for the transport of communication data may well differ from the network topology for the exchange of messages. The user of the communication system has the advantage that he only has to have an ATM network connection, and not also an Ethernet connection.

The message processing takes place particularly advantageously in the second central device, because in this way previously customary peripheral devices can also be involved in the message control sequence, so that a mixture of previously customary devices of a private branch exchange with novel devices of a new private branch exchange can be operated and controlled in any desired form. In a development of the arrangement described another embodiment of the invention, control messages for the connection control of a switching unit are generated particularly advantageously in the central control device and transmitted to the second decentralized communication devices, or are used for controlling the switching unit in the case of mixed arrangements. In this way, connections can be established in the entire area of the switching device, irrespective of whether the

communication subscribers are connected to novel devices or to customary devices.

### BRIEF DESCRIPTION OF THE INVENTION

5 Exemplary embodiments of the invention are explained in more detail below on the basis of figures:

figure Figure 1 shows a conventional communication arrangement<sub>7</sub>.

10 figure Figure 2 shows an example of a communication arrangement with decentralized devices<sub>7</sub>.

figure Figure 3 shows a network structure comprising a central device and a number of decentralized devices<sub>7</sub>.

15 figure Figure 4 illustrates the linking of a decentralized device to a central device<sub>7</sub>.

figure Figure 5 illustrates an advantageous configuration of an arrangement for coupling messages on the basis of an ATM network<sub>7</sub>.

20 figure Figure 6 shows a view of a detail of the coupling of decentralized devices to a central control device via an ATM network.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

25 Figure 1 shows an example of a known private branch exchange 150 with a central control device. This private branch exchange is connected to two peripheral devices P1 and P2, to which there is respectively connected a communication terminal KE1 and KE2  
30 operating on a digital or analog basis. These peripheral devices P1 and P2 are accommodated in the same spatial area as the first central device Z1. They are consequently located in the same space or in the same cabinet as it. The terminals occupy defined time  
35 slots of a PCM data stream (Puls Code Modulation) with communication data. In this case, these analog or digital communication terminals KE1 and KE2 are connected via interface modules SLMO1 and SLMO2, which feed to the PCM data stream, or remove from it, data

5 Likewise represented are signaling connections 110 and 210, via which message traffic with a central control can take place. In the case of this representation it should be noted that ~~only~~ a logical representation of the connections is shown in the topology for individual  
10 connections, and that this is not a physical representation. In the technical realization of these networks, the transport data and the messages can be transmitted over the same connection medium without restriction.

30 To be specific, messages 2, which are to be exchanged  
between the central device ZE2 and the peripheral  
devices P1, P2, are collected and distributed by a  
message device DCL. The setting-up and clearing-down  
of connections is controlled by means of the Call  
35 Processing CP, with the Call Processing using for this  
purpose, ~~inter-alia~~ for example, device-specific  
interface functions DH, which are realized for example  
in the form of program modules. In particular, setting  
commands 1 for the switching unit MTS are generated.

Such a setting command essentially controls which input of the switching unit is to be connected to which output in order to provide a communication connection via this switching device. In such a known communication arrangement, control and connection functions are consequently performed by a single spatially integrated functional unit of the communication network. In the case of such a center-oriented configuration, problems arise because all the data to be transported have to be fed to the central device ZE1. This is the case even if, for example, two communication terminals which are connected to the same peripheral device P1 want to communicate with each other. Such a centrally oriented arrangement also gives rise to high expenditure on cabling, because both the control lines and the communication lines have to be routed to the central device ZE1. It is not possible for peripheral devices to be distributed over a wide area, because the time-critical message traffic via the control lines with the aid of a HDLC protocol cannot take place over links comprising lines of any desired length. To be able to achieve a greater area coverage by means of such devices, the coupling of a number of devices would be conceivable, although the advantages of a single system in the form of central interfaces, and for example central facility control, would be lost. Furthermore, when linking them up, additional trunk modules would have to be installed and additional connecting cables would have to be laid for their connection. Such private branch exchanges also cannot be modularly expanded to whatever extent is desired, because the switching unit MTS for example can only be provided as a complete unit. This means that, in an extreme case, a new switching unit with, for example, 4096 ports must be purchased and installed for a single additional connection. The transmission rate in such systems is limited for example by the possibility that only a maximum of 64 kbits, or some other administratively fixed or technically dictated

10085555-032100

volume of data which is prescribed by the ISDN standard, can be transmitted per time slot. In this case, different data rates for individual communication connections are not possible.

5

Figure 2 shows an example of an arrangement for setting up, clearing down and operating communication connections via decentralized devices which are controlled by a central device. Here, for example, a private branch exchange 250 is represented. The same component parts of the device are denoted by the same reference numerals in figure 2 as in figure 1. It is notable in the case of this communication arrangement that there are a separate transport network 700 and an independent control network 310/410. Such a setup of an exchange has the advantage that already existing networks, in the form of public or private networks, can be used for the transport network. What is more, only the control network has to be routed to the central device ZE2.

The digital or analog communication terminals KE1 and KE2 are represented in this representation in such a way that they are respectively connected to interface modules SLMO1 and SLMO2. Without restricting the invention, however, such terminals which can be connected to the transport network 700 directly, bypassing the interface modules SLMO, are also conceivable and able to be integrated in such an arrangement 250. Consequently, ATM terminals or IP-based (Internet Protocol) terminals can also be directly connected.

As can also be seen, the decentralized devices DZ1 and DZ2 in each case have decentralized switching devices CS1 and CS2, which may for example take the form of ATM access devices. Similarly, it can be directly seen that the switching unit MTS0 is no longer used for



connection tasks. These connection tasks are instead undertaken by the transport network.

For controlling the decentralized switching devices CS1  
5 and CS2, at least one item of control information is in  
each case transmitted by means of a dedicated message  
to these switching devices via the control lines 410  
and 310, which are component parts of a control  
10 network, for setting up and clearing down the  
communication connection. This control information  
contains includes time-slot-related control  
information, derived from the control instructions for  
the switching unit MTS. Furthermore, the figure  
reveals that a conversion from PCM data into ATM cell  
15 data is carried out on a data link 300 or 400. It  
should be noted here that the use of an ATM network as  
a transport network serves here merely as an exemplary  
embodiment. Internet and other IP connections, or even  
TDM connections, likewise come into consideration as  
20 transport networks. The selection of the respective  
network is in this case dependent on the intended use  
and extends over the entire spectrum of available  
networks, both in the narrowband range and in the  
broadband range.

25 Because the communication connections to the central  
device ZE2 are no longer needed in such arrangements,  
in the case of this configuration it is not necessary  
for connection fees, for instance for both connections  
30 from DZ1 and DZ2 to the central device ZE2 via public  
lines, for example fixed lines, to be paid, as  
previously the case with a remote peripheral device PE  
in a device 150 from figure 1 when there is  
communication from PE1 to PE2. For controlling the  
35 setting-up of the connection and the associated  
exchange of messages, a transport-network-dependent  
call processing is carried out on the decentralized  
switching devices CS1 and CS2, but is restricted  
essentially to basic call functionality. The

10088553 "032100"

facilities are in this case realized and provided by the central control ZE2. Connections between the various central devices are controlled by the central devices ZE2 by means of messages which contain control  
5 information.

The advantages of such an arrangement are that it is capable of both narrowband and broadband operation. A possibly used backplane in the decentralized device  
10 would have to be newly developed, however, in order to allow broadband connections to be established, in contrast to TDM backplanes. Furthermore, the transport network can be set up both on public networks and on private networks, or else on a mixture of the two.  
15 Furthermore, there is the possibility of assigning to the central device ZE2 decentralized devices that are an unlimited distance away, so that even very large installations can be provided with such a private branch exchange, which in turn serve for supplying  
20 widespread areas with communication connections. In this case, because a central device is retained, there is the possibility of continuing to use already existing software, with minimal changes, for the control. On the other hand, new methods of control  
25 would have to be developed and a new mechanism for ensuring consistency of a distributed database would have to be created if the control, like the switching unit, were likewise distributed. A further advantage of such a device 250 in comparison with networked  
30 systems of the type 150 is that the distributed system behaves like a single telephone switching device and therefore facilities which are merely implemented across the exchange can be operated there. This dispenses with the need to convert individual  
35 facilities to make them able to operate on a network. For this reason, central interfaces and applications can likewise continue to be used.

10088688-032102

Figure 3 shows by an example, in a schematized form, the setup of a private branch exchange 450. There can be seen a central control device ZE2, which is in connection with second decentralized communication devices DZ1, DZ10 and DZ20 via second communication connections 1001, 1010 and 1020. These connections are generally long-distance connections, with which the less time-critical coupling of various first decentralized communication devices can be accomplished. It is indicated by the dots between DZ1 and DZ10 in the figure that any number of decentralized devices DZ can be connected via second communication connections to the central device. Examples of such networks for long-distance connection which may be given are ATM networks, Ethernets, or other IP-transporting networks. Assigned to each second decentralized device are first decentralized devices. These second decentralized devices are in contact with the first decentralized devices via a first communication connection. The message traffic from the first decentralized device to the second decentralized device is handled via this communication connection, which at the same time serves as a relay station for the communication with the central control device ZE2.

Connected to the second decentralized device DZ1 are first decentralized devices DZ12, DZ15 and DZ19, each via first communication connections 2012, 2015 and 2019. The dots between the first decentralized devices DZ12 and DZ15 are intended to indicate that it is possible within the limits of the technical possibilities of a second decentralized device for any number of such first decentralized devices to be connected to the latter via respective first communication connections. Furthermore, connected to the second decentralized device DZ10 are first decentralized devices DZ102, DZ105 and DZ108 via first communication connections 2102, 2105 and 2108. The functionality of the second decentralized devices for

the message traffic is essentially identical. For the exchange of messages with the central control device ZE2, first decentralized devices DZ202, DZ207 and DZ237 are connected to the second decentralized device DZ20  
5 via first communication connections 2202, 22207 and 2237. In a favorable configuration of an arrangement, the first decentralized devices DZ12 to DZ 237 are configured as interface modules for communication terminals SLMO. The first communication connections  
10 2012 to 2237 to the respective first decentralized devices are generally connections via which time-critical control messages are transmitted. For this purpose, the HDLC method is used between the first decentralized device and the second decentralized  
15 device as the first communication protocol. These first communication connections may advantageously take the form of a backplane bus of a second decentralized device. This variant of the configuration allows modules which are used in conventional systems  
20 for the connection of communication terminals to be used as first decentralized devices.

The second decentralized communication devices are connected over relatively great distances, via LANs  
25 (Local Area Networks) or WANs (Wide Area Networks) such as Ethernet or ATM connections for example, to the central control device ZE2. On these second communication connections, a layer protocol of the ISO type (Open Systems Interconnect) of protocol is  
30 implemented, comprising seven layers, the lowermost layer representing the physical layer, the second layer the link layer, the third the network layer, the fourth the transport layer, the fifth the session control, the sixth the data presentation and the seventh the  
35 application layer. In this layer protocol, standardized in accordance with ISO IS8802, each layer uses the services of the layer lying under it. Messages which are transmitted with the aid of this layer protocol consequently receive additional

10088688-033102

information successively at each layer, thus producing a data structure in which the original message has seven layer-specific elements of information added to it. This process is also known as "packing" the information, whereas the reverse process, in which the corresponding elements of the structure are returned layer-dependently to the respective layers to produce the original message, is known as "unpacking". Theoretically, the possibility of interleaving a number of such protocols would also exist, but would necessitate a considerable administrative effort and would lead to increased loading of the second communication connection during the data transmission, because the information on the layer organization of the other protocol has to be additionally transmitted along with the actual message itself.

For converting the HDLC protocol used on the first communication connection into the OSI protocol layers used on the second communication connection, for example in the form of the layer sequences Ethernet/IP/TCP or ATM/IP/TCP, there is in a respective second decentralized device DZ1 to DZ20 in each case a device for protocol transformation of the messages to be exchanged, this device in each case performing the conversion by unpacking the message completely from the protocol used and then packing it into the other protocol and passing it on. As the figure further reveals, various first decentralized devices and second decentralized devices form groups. These groups are devices which are spatially close together and may, for example, be accommodated in different buildings, which are connected to one another by a private branch exchange. For administering the message traffic from the first decentralized devices to the central control device, in the second decentralized device there is provided a message collecting and distributing device, which acts virtually as a representative communication partner of the first decentralized devices and

10088668, 032102

coordinates the message traffic between the central control device and the first decentralized devices.

Previously customary peripheral devices are also linked  
5 to ZE2 via a device DCL (not represented). An additional software module decides whether messages are sent as before via DCL or via the IP path and consequently via the Ethernet connection. In the opposite direction, this software similarly forms both  
10 inputs (DCL and IP) in one. Consequently, the additional software module provides a uniform interface in the direction of the system software and covers the split into two different paths and types of transmission.

15 In connection with the reference numerals which are used in the various figures, it must also be noted that the same reference numerals also concern communication devices or component parts of communication  
20 arrangements of the same type. The second communication connections to the central control device may be configured on a wide variety of communication media, it being possible for the Internet protocol to be used on layer 3 and the Transmission Control  
25 Protocol TCP to be used on layer 4. Various mixed variants are conceivable here. This protocol structure achieves the effect that, as from layer 3, messages can be exchanged over a wide variety of communication media system-wide.

30 Figure 4 shows a view of a detail of the private branch exchange 450 which is represented in figure 3. To illustrate individual elements of the second decentralized device DZ1 and of the central control  
35 device ZE2. As can be seen, a first communication connection KV1 is configured for example as a backplane bus of a second decentralized device DZ1, the first communication connections 2012 to 2019 run there. In a decentralized switching device CS1 there is provided a

10085553 "034102"

conversion device HDLC1, IP1, which converts the HDLC protocol used on the first communication connection KV1 into the OSI layer protocols used on the second communication connection 1001, and vice versa. The  
5 decentralized switching device CS1 has a port 700 to the transport network. For the coordination of the message traffic between the first decentralized devices and the central control device there is in the second decentralized device DZ1 a message collecting and  
10 distributing device HDLC1. There, messages from first decentralized devices are collected and passed on in a bundled form via the second communication connection 1001 to the central control device ZE2. In the reverse direction, the control messages arriving from the  
15 central control device are distributed to the respective addressees in the second decentralized device. To be able to evaluate and process in a coordinated manner the various messages which are sent to the different second decentralized communication  
20 devices, or which are sent in the opposite direction from the various second decentralized communication devices to the central control device ZE2, there is in the central control device a connection device IP2, which is capable of evaluating the protocol information  
25 on the second communication connection 1001 and recreating the original messages, or packing them in the reverse direction. The connection devices IP1 and IP2 may in this case operate on the lowermost layers with the Ethernet protocol. This connection device is  
30 in connection with a message processing and control device DCL2, which in the case of the central control device ZE2 possibly prioritizes, sorts, passes on for processing or sends messages also arriving from peripheral devices via DCL, or sent from it.

35 As can be further seen, in the arrangement represented the switching unit MTS no longer performs any function. However, it is conceivable that a peripheral device, which is represented in figure 1, is connected to ZE2

1008553 "032103"

via a decentralized switching device of the same type as CS1, the message traffic with ZE2 continuing to be handled by means of HDLC via DCL and DCL2. In this way, conventional, already operating private branch  
5 exchanges can be combined with exchanges of a newer type and this type of arrangement is appropriate as a migration solution for a transitional period of time. For the case in which older devices of the type of a switching device 150 are connected, the switching unit  
10 MTS is still required in order to perform the connecting function in the area of devices of the type 150.

DCL2, as an additional software module, brings the two message paths via DCL and IP2 together and thus covers  
15 the existence of two interfaces for the central control ZE2.

Figure 5 shows a special embodiment of a private branch exchange 450, in which an ATM network is used as the  
20 second communication connection between the central control device. In the case of this special configuration of the arrangement, the same ATM network can be used for the transport network 700 and for the accomplishment of the message traffic via second  
25 communication connections by means of the IP protocol. In this case, the transport network 700 and the control network which is formed by the second communication connections 1020 to 1001 may have a complete different logical structure.

30 This special embodiment is particularly favorable because it is possible in this case to dispense with Ethernet connections to the second decentralized devices DZ20 to DZ1 and only a single network  
35 infrastructure has to be provided, for example in the form of an ATM network. However, this type of physical coupling for the accomplishment of the message traffic requires adaptation measures in the area of the central control device ZE2. For this purpose, the central

10085555-032400



control device ZE2 is divided into two subunits EZE2 and ZZE2, which are connected to each other by a connecting line Z2020. In this case, the connection to the ATM network is established via the first central unit EZE2, while the message collection evaluation, processing and distribution takes place in the second central device ZZE2. More details on this emerge from the description of figure 6.

Figure 6 shows a partial view of the private branch exchange 450 which is represented in figure 5. Here, the individual components of the decentralized device DZ1 and of the first central unit EZE2 and of the second central unit ZZE2 can be seen. Realized in the second decentralized device DZ1, for example by means of a backplane bus, are first communication connections 2015 and 2012, via which a communication of the first decentralized communication devices DZ15 and DZ12 with a device HDLC1 takes place in accordance with the HDLC protocol.

For example, communication terminals are connected to these first decentralized devices. The device HDLC1 serves as a message collecting and distributing device, which terminates the HDLC protocol in the direction of the communication terminals. The messages are passed to the device IP1, which serves for packing the messages into the Internet protocol. HDLC1 and IP1 consequently form the converting device from HDLC to IP. The IP packets are fed to an ATM access device ATM1 and converted there into an ATM cell stream.

The conversion of the data which are transmitted in accordance with the Internet protocol into an ATM cell stream for the device ATM1 may take place either in IPM1 or in ATM1. The data connections I100 and I200 represented are not necessarily lines in the physical sense but functional block interfaces, which may also

METHOD AND ARRANGEMENT FOR COUPLING MESSAGES OF A  
CENTRAL CONTROL DEVICE WITH DECENTRALIZED COMMUNICATION  
DEVICES

5 CLAIM FOR PRIORITY

This application claims priority to International Application No. PCT/DE00/03175 which was published in the German language on September 13, 2000.

10 TECHNICAL FIELD OF THE INVENTION

The invention relates to a method and an arrangement for transporting messages, and in particular, to control messages, in a switching device such as a private branch exchange set up over a large area, in  
15 which a number of decentralized devices are controlled from a central device.

BACKGROUND OF THE INVENTION

The requirements imposed on communication  
20 infrastructure installations, such as private branch exchanges for example, are constantly increasing. The cause for the increasing requirements with regard to the data transmission capacity of switching devices lies in the constantly increasing demand for voice,  
25 video and data communication and the consequence that networks of broader bands have to be used for establishing connections. The cause for greater flexibility with regard to the number of subscribers which can be connected to switching devices lies in the  
30 requirement for the infrastructure to keep pace technically with the flexibility of the business processes of the users of the communication device. This results in a great demand for flexible modularly expandable private branch exchanges.

35 Current devices are based on time-slot multiplexing connections between communication terminals which are set up by means of a switching unit, for which purpose commands which indicate which defined time slot of an

1008888-032102



incurred and the communication partners would have to be provided with more resources, for example memories.

#### SUMMARY OF THE INVENTION

5 The invention is based on a method and an arrangement for coupling messages of a central control device with a decentralized communication device which are not subject to any restrictions with regard to the distance between the central device and the decentralized  
10 device.

In one embodiment of the invention, the time-critical message traffic is ensured in a particularly advantageous way by an especially suitable  
15 communication protocol on just one partial connection link. On a further partial connection, in particular a long-distance connection, another, specifically suitable, communication protocol can then be used. This advantageously achieves the effect that already  
20 existing modules in decentralized devices can continue to be used, without the length of the connecting lines to a central control device being subject to restrictions. Similarly, the message transport is advantageously optimized, because the messages are just  
25 transported directly and so there is no longer the additional computational effort which would arise when one protocol is packed into another protocol. Similarly, fewer data therefore have to be transmitted, whereby time advantages and higher data capacities in  
30 message transport are attainable.

Standardized communication protocols, set up in accordance with the OSI layer model (Open Systems Interconnect), are advantageously used, because  
35 standardized devices (chips, protocol stacks) for such protocols are available on the market, making it easily possible to meet the required increase in the transmission performance on a connection by using faster devices. Since the messages themselves are

10088888-032100

transmitted on each partial connection link, in an optimum way the volume of user data is transmitted and the data transmission structures can remain restricted to the necessary minimum.

5

In the case of a first protocol, the HDLC method is advantageously used on a lowermost layer level, because in this way the modules in the decentralized devices, which today already have an HDLC interface, can continue to be used. This HDLC method is advantageously combined with a second communication protocol, which on the lowermost layers either has an Ethernet protocol or transmits there in accordance with the ATM protocol. In this way it is possible to use networks that are established and available for long-distance transmission, it being possible as from layer 3 to use the same protocol layers again for the network switching and transport, in spite of the different fundamentals. For this reason, mixed configurations of a wide variety of protocols and networks can also be set up without any technical development effort. The ATM transmission method is advantageously particularly suitable for use on a long-distance connection, because different transmission qualities can be set up on the connections, allowing defined time requirements to be met in the message traffic.

In one aspect of the invention, the Internet protocol is advantageously used on the network layer, because this Internet protocol is already available for a wide variety of transmission media, and consequently the same transport and network switching services can be used for the various transmission media.

In another aspect of the invention, control messages are advantageously transmitted, because in this case there are hard time requirements of the communication partners, according to the method describes no changes are required in the decentralized devices, transmission

10086666-032102

methods for control messages already exist for the HDLC method, because they have already been implemented in the case of current devices, and because a wide variety of networks can be used for the long-distance  
5 connections.

One embodiment of the invention is advantageously suitable for the coupling of a number of decentralized devices to a central control, because messages are  
10 collected coordinated and distributed in a decentralized manner and have to be transmitted in a bundled manner on a line to the centre. In the bundling, a number of messages can be advantageously packed into an IP packet and consequently the  
15 administrative effort of the protocols can be reduced. The ratio of user data to protocol data is better as a result, and consequently there is a reduced load on the network.

20 For the administration of a number of decentralized devices, it is advantageously possible to set up groups, for which messages are respectively collected and distributed, because in this way message collecting and distributing devices which can already be used for  
25 central devices of a known type can be used in decentralized devices.

For the case in which a number of groups of decentralized devices are administered, a sorting of  
30 the messages is advantageously carried out in the central control device before they are processed, because in this way a unique group-specific prioritizing and processing of the messages is made possible.

35 At least two types of connecting lines, on which different transmission protocols are implemented, are used advantageously in an arrangement for coupling messages between a decentralized device and a central

10088888-033100

control device. For the exchange of messages in the local exchange area, HDLC-based protocols are advantageously used, because in this way already known and existing decentralized devices on the basis of the HDLC protocol with their critical time requirements in decentralized devices can continue to be used, and Internet connections or ATM connections, for which standardized products are established on the market, can be used for the long-distance connections of these decentralized devices to the central control device, so that, with regard to the transmission capacity, a broad spectrum can be easily covered by the acquisition of products generally available on the market.

Depending on the required transmission capacity and distance, various media, which are available for the most diverse networks, can be advantageously used for the long-distance connections. For this reason, in the case of a number of decentralized devices, mixed configurations comprising a wide variety of transmission media are also possible.

In another embodiment of the invention, first communication connections advantageously take the form of a backplane bus, because in this way already existing modules can be taken over unchanged from conventional devices into new devices as decentralized devices. Likewise, this type of configuration requires less additional development effort for the development of decentralized devices.

The protocol conversion takes place advantageously in the area of a decentralized device, because in this way the time-critical transmission in accordance with the HDLC method can be best ensured. Similarly, there is no need for additional devices which carry out a protocol conversion in the area of the private branch exchange. Moreover, converting devices arranged decentrally in this way are also able to be adapted

exactly in their conversion capacity to the communication volume of the respective decentralized device, and consequently can be used particularly efficiently.

5

A special device, which sorts and distributes messages which are received by it from various second decentralized devices, or are to be sent to the latter, is provided advantageously in the central control  
10 device for the administration of second communication connections. In this way, a defined message processing over a number of decentralized devices is ensured and the possibility that messages over a number of decentralized devices can also be processed in a  
15 prioritizable manner is advantageously ensured.

For the case in which the second communication connection is formed as an ATM network, the central control device is advantageously divided into two  
20 units, of which one has an ATM access, while the other may be connected to this unit via a current Ethernet connection. This type of configuration has the advantage that customary central control devices can continue to be used largely unchanged and do not have  
25 to be further developed for access to an ATM network. Furthermore, the ATM network can be used for the transmission both of control messages and for the transport of communication data between the terminals, only the Internet protocol having to be implemented on  
30 layer 3 of the communication protocol for the transmission of the control messages, and the transfer to the central control device to the Ethernet can also take place on this layer. It is consequently possible to dispense with Ethernet connections between the  
35 central control device and the decentralized communication devices. It should be noted here that the network topology for the transport of communication data may well differ from the network topology for the exchange of messages. The user of the communication

10085533-033406



system has the advantage that he only has to have an ATM network connection, and not also an Ethernet connection.

5 The message processing takes place advantageously in the second central device, because in this way previously customary peripheral devices can also be involved in the message control sequence, so that a mixture of previously customary devices of a private  
10 branch exchange with novel devices of a new private branch exchange can be operated and controlled in any desired form. In another embodiment of the invention, control messages for the connection control of a switching unit are generated advantageously in the  
15 central control device and transmitted to the second decentralized communication devices, or are used for controlling the switching unit in the case of mixed arrangements. In this way, connections can be established in the entire area of the switching device,  
20 irrespective of whether the communication subscribers are connected to novel devices or to customary devices.

#### BRIEF DESCRIPTION OF THE INVENTION

Exemplary embodiments of the invention are explained in  
25 more detail below on the basis of figures:

Figure 1 shows a conventional communication arrangement.

Figure 2 shows an example of a communication  
30 arrangement with decentralized devices.

Figure 3 shows a network structure comprising a central device and a number of decentralized devices.

Figure 4 illustrates the linking of a decentralized device to a central device.

35 Figure 5 illustrates an advantageous configuration of an arrangement for coupling messages on the basis of an ATM network.

Figure 6 shows a view of a detail of the coupling of decentralized devices to a central control device via an ATM network.

5        DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figure 1 shows an example of a known private branch exchange 150 with a central control device. This private branch exchange is connected to two peripheral devices P1 and P2, to which there is respectively  
10 connected a communication terminal KE1 and KE2 operating on a digital or analog basis. These peripheral devices P1 and P2 are accommodated in the same spatial area as the first central device Z1. They are consequently located in the same space or in the  
15 same cabinet as it. The terminals occupy defined time slots of a PCM data stream (Puls Code Modulation) with communication data. In this case, these analog or digital communication terminals KE1 and KE2 are connected via interface modules SLM01 and SLM02, which  
20 feed to the PCM data stream, or remove from it, data which are intended for the respective terminals, or come from the respective terminals, via time slots established by control messages. Two PCM data streams are denoted in the figure by 100 and 200, respectively.  
25 Likewise represented are signaling connections 110 and 210, via which message traffic with a central control can take place. In the case of this representation it should be noted that a logical representation of the connections is shown in the topology for individual  
30 connections, and that this is not a physical representation. In the technical realization of these networks, the transport data and the messages can be transmitted over the same connection medium without restriction.

35

Also represented are peripheral devices P1 and P2, and also the supply modules LTUC1 and LTUC2, which regulate the data traffic to the interface modules, for example SLM01 and SLM02, of the respective peripheral devices.

10088588-03240

In this case, the peripheral device is fed control messages via the line 110 and the peripheral device P2 is fed control messages via the line 210. It can be clearly seen in the case of this known private branch  
5 exchange that, with this arrangement of the individual components of the switching device, both the information to be transported and the signaling information, exchanged by means of coordinated message traffic, have to be fed to a central device ZE1.

10

To be specific, messages 2, which are to be exchanged between the central device ZE2 and the peripheral devices P1, P2, are collected and distributed by a message device DCL. The setting-up and clearing-down  
15 of connections is controlled by means of the Call Processing CP, with the Call Processing using for this purpose, for example, device-specific interface functions DH, which are realized for example in the form of program modules. In particular, setting  
20 commands 1 for the switching unit MTS are generated. Such a setting command essentially controls which input of the switching unit is to be connected to which output in order to provide a communication connection via this switching device. In such a known  
25 communication arrangement, control and connection functions are consequently performed by a single spatially integrated functional unit of the communication network. In the case of such a center-oriented configuration, problems arise because the data  
30 to be transported have to be fed to the central device ZE1. This is the case even if, for example, two communication terminals which are connected to the same peripheral device P1 want to communicate with each other. Such a centrally oriented arrangement also  
35 gives rise to high expenditure on cabling, because both the control lines and the communication lines have to be routed to the central device ZE1. It is not possible for peripheral devices to be distributed over a wide area, because the time-critical message traffic

10088888 "03310"

via the control lines with the aid of a HDLC protocol cannot take place over links comprising lines of any desired length. To be able to achieve a greater area coverage by means of such devices, the coupling of a number of devices would be conceivable, although the advantages of a single system in the form of central interfaces, and for example central facility control, would be lost. Furthermore, when linking them up, additional trunk modules would have to be installed and additional connecting cables would have to be laid for their connection. Such private branch exchanges also cannot be modularly expanded to whatever extent is desired, because the switching unit MTS for example can only be provided as a complete unit. This means that, in an extreme case, a new switching unit with, for example, 4096 ports must be purchased and installed for a single additional connection. The transmission rate in such systems is limited for example by the possibility that only a maximum of 64 kbits, or some other administratively fixed or technically dictated volume of data which is prescribed by the ISDN standard, can be transmitted per time slot. In this case, different data rates for individual communication connections are not possible.

Figure 2 shows an example of an arrangement for setting up, clearing down and operating communication connections via decentralized devices which are controlled by a central device. Here, for example, a private branch exchange 250 is represented. The same component parts of the device are denoted by the same reference numerals in figure 2 as in figure 1. It is notable in the case of this communication arrangement that there are a separate transport network 700 and an independent control network 310/410. Such a setup of an exchange has the advantage that already existing networks, in the form of public or private networks, can be used for the transport network. What is more,

the control network has to be routed to the central device ZE2.

The digital or analog communication terminals KE1 and KE2 are represented in this representation in such a way that they are respectively connected to interface modules SLM01 and SLM02. Without restricting the invention, however, such terminals which can be connected to the transport network 700 directly, bypassing the interface modules SLM0, are also conceivable and able to be integrated in such an arrangement 250. Consequently, ATM terminals or IP-based (Internet Protocol) terminals can also be directly connected.

As can also be seen, the decentralized devices DZ1 and DZ2 in each case have decentralized switching devices CS1 and CS2, which may for example take the form of ATM access devices. Similarly, it can be directly seen that the switching unit MTS0 is no longer used for connection tasks. These connection tasks are instead undertaken by the transport network.

For controlling the decentralized switching devices CS1 and CS2, at least one item of control information is in each case transmitted by means of a dedicated message to these switching devices via the control lines 410 and 310, which are component parts of a control network, for setting up and clearing down the communication connection. This control information includes time-slot-related control information, derived from the control instructions for the switching unit MTS. Furthermore, the figure reveals that a conversion from PCM data into ATM cell data is carried out on a data link 300 or 400. It should be noted here that the use of an ATM network as a transport network serves here merely as an exemplary embodiment. Internet and other IP connections, or even TDM connections, likewise come into consideration as transport networks. The

1008555 "032102

selection of the respective network is in this case dependent on the intended use and extends over the entire spectrum of available networks, both in the narrowband range and in the broadband range.

5

Because the communication connections to the central device ZE2 are no longer needed in such arrangements, in the case of this configuration it is not necessary for connection fees, for instance for both connections from DZ1 and DZ2 to the central device ZE2 via public lines, for example fixed lines, to be paid, as previously the case with a remote peripheral device PE in a device 150 from figure 1 when there is communication from PE1 to PE2. For controlling the setting-up of the connection and the associated exchange of messages, a transport-network-dependent call processing is carried out on the decentralized switching devices CS1 and CS2, but is restricted essentially to basic call functionality. The facilities are in this case realized and provided by the central control ZE2. Connections between the various central devices are controlled by the central devices ZE2 by means of messages which contain control information.

25

The advantages of such an arrangement are that it is capable of both narrowband and broadband operation. A possibly used backplane in the decentralized device would have to be newly developed, however, in order to allow broadband connections to be established, in contrast to TDM backplanes. Furthermore, the transport network can be set up both on public networks and on private networks, or else on a mixture of the two. Furthermore, there is the possibility of assigning to the central device ZE2 decentralized devices that are an unlimited distance away, so that even very large installations can be provided with such a private branch exchange, which in turn serve for supplying widespread areas with communication connections. In

10088585 032100

this case, because a central device is retained, there is the possibility of continuing to use already existing software, with minimal changes, for the control. On the other hand, new methods of control would have to be developed and a new mechanism for ensuring consistency of a distributed database would have to be created if the control, like the switching unit, were likewise distributed. A further advantage of such a device 250 in comparison with networked systems of the type 150 is that the distributed system behaves like a single telephone switching device and therefore facilities which are merely implemented across the exchange can be operated there. This dispenses with the need to convert individual facilities to make them able to operate on a network. For this reason, central interfaces and applications can likewise continue to be used.

Figure 3 shows by an example, in a schematized form, the setup of a private branch exchange 450. There can be seen a central control device ZE2, which is in connection with second decentralized communication devices DZ1, DZ10 and DZ20 via second communication connections 1001, 1010 and 1020. These connections are generally long-distance connections, with which the less time-critical coupling of various first decentralized communication devices can be accomplished. It is indicated by the dots between DZ1 and DZ10 in the figure that any number of decentralized devices DZ can be connected via second communication connections to the central device. Examples of such networks for long-distance connection which may be given are ATM networks, Ethernets, or other IP-transporting networks. Assigned to each second decentralized device are first decentralized devices. These second decentralized devices are in contact with the first decentralized devices via a first communication connection. The message traffic from the first decentralized device to the second decentralized

device is handled via this communication connection, which at the same time serves as a relay station for the communication with the central control device ZE2.

5 Connected to the second decentralized device DZ1 are first decentralized devices DZ12, DZ15 and DZ19, each via first communication connections 2012, 2015 and 2019. The dots between the first decentralized devices DZ12 and DZ15 are intended to indicate that it is  
10 possible within the limits of the technical possibilities of a second decentralized device for any number of such first decentralized devices to be connected to the latter via respective first communication connections. Furthermore, connected to  
15 the second decentralized device DZ10 are first decentralized devices DZ102, ZD105 and DZ108 via first communication connections 2102, 2105 and 2108. The functionality of the second decentralized devices for the message traffic is essentially identical. For the  
20 exchange of messages with the central control device ZE2, first decentralized devices DZ202, DZ207 and DZ237 are connected to the second decentralized device DZ20 via first communication connections 2202, 22207 and 2237. In a favorable configuration of an arrangement,  
25 the first decentralized devices DZ12 to DZ 237 are configured as interface modules for communication terminals SLMO. The first communication connections 2012 to 2237 to the respective first decentralized devices are generally connections via which time-  
30 critical control messages are transmitted. For this purpose, the HDLC method is used between the first decentralized device and the second decentralized device as the first communication protocol. These first communication connections may advantageously take  
35 the form of a backplane bus of a second decentralized device. This variant of the configuration allows modules which are used in conventional systems 150 for the connection of communication terminals to be used as first decentralized devices.

10086555, 032102



10085533 "032100"

The second decentralized communication devices are connected over relatively great distances, via LANs (Local Area Networks) or WANs (Wide Area Networks) such as Ethernet or ATM connections for example, to the central control device ZE2. On these second communication connections, a layer protocol of the ISO type (Open Systems Interconnect) of protocol is implemented, comprising seven layers, the lowermost layer representing the physical layer, the second layer the link layer, the third the network layer, the fourth the transport layer, the fifth the session control, the sixth the data presentation and the seventh the application layer. In this layer protocol, standardized in accordance with ISO IS8802, each layer uses the services of the layer lying under it. Messages which are transmitted with the aid of this layer protocol consequently receive additional information successively at each layer, thus producing a data structure in which the original message has seven layer-specific elements of information added to it. This process is also known as "packing" the information, whereas the reverse process, in which the corresponding elements of the structure are returned layer-dependently to the respective layers to produce the original message, is known as "unpacking". Theoretically, the possibility of interleaving a number of such protocols would also exist, but would necessitate a considerable administrative effort and would lead to increased loading of the second communication connection during the data transmission, because the information on the layer organization of the other protocol has to be additionally transmitted along with the actual message itself.

35

For converting the HDLC protocol used on the first communication connection into the OSI protocol layers used on the second communication connection, for example in the form of the layer sequences

10055555 "032102"

Ethernet/IP/TCP or ATM/IP/TCP, there is in a respective second decentralized device DZ1 to DZ20 in each case a device for protocol transformation of the messages to be exchanged, this device in each case performing the conversion by unpacking the message completely from the protocol used and then packing it into the other protocol and passing it on. As the figure further reveals, various first decentralized devices and second decentralized devices form groups. These groups are devices which are spatially close together and may, for example, be accommodated in different buildings, which are connected to one another by a private branch exchange. For administering the message traffic from the first decentralized devices to the central control device, in the second decentralized device there is provided a message collecting and distributing device, which acts virtually as a representative communication partner of the first decentralized devices and coordinates the message traffic between the central control device and the first decentralized devices.

Previously customary peripheral devices are also linked to ZE2 via a device DCL (not represented). An additional software module decides whether messages are sent as before via DCL or via the IP path and consequently via the Ethernet connection. In the opposite direction, this software similarly forms both inputs (DCL and IP) in one. Consequently, the additional software module provides a uniform interface in the direction of the system software and covers the split into two different paths and types of transmission.

In connection with the reference numerals which are used in the various figures, it must also be noted that the same reference numerals also concern communication devices or component parts of communication arrangements of the same type. The second communication connections to the central control device

may be configured on a wide variety of communication media, it being possible for the Internet protocol to be used on layer 3 and the Transmission Control Protocol TCP to be used on layer 4. Various mixed  
5 variants are conceivable here. This protocol structure achieves the effect that, as from layer 3, messages can be exchanged over a wide variety of communication media system-wide.

10 Figure 4 shows a view of a detail of the private branch exchange 450 which is represented in figure 3. To illustrate individual elements of the second decentralized device DZ1 and of the central control device ZE2. As can be seen, a first communication  
15 connection KV1 is configured for example as a backplane bus of a second decentralized device DZ1, the first communication connections 2012 to 2019 run there. In a decentralized switching device CS1 there is provided a conversion device HDLC1, IP1, which converts the HDLC  
20 protocol used on the first communication connection KV1 into the OSI layer protocols used on the second communication connection 1001, and vice versa. The decentralized switching device CS1 has a port 700 to the transport network. For the coordination of the  
25 message traffic between the first decentralized devices and the central control device there is in the second decentralized device DZ1 a message collecting and distributing device HDLC1. There, messages from first decentralized devices are collected and passed on in a  
30 bundled form via the second communication connection 1001 to the central control device ZE2. In the reverse direction, the control messages arriving from the central control device are distributed to the respective addressees in the second decentralized  
35 device. To be able to evaluate and process in a coordinated manner the various messages which are sent to the different second decentralized communication devices, or which are sent in the opposite direction from the various second decentralized communication

10086666 032102

As can be further seen, in the arrangement represented the switching unit MTS no longer performs any function. However, it is conceivable that a peripheral device, which is represented in figure 1, is connected to ZE2 via a decentralized switching device of the same type as CS1, the message traffic with ZE2 continuing to be handled by means of HDLC via DCL and DCL2. In this way, conventional, already operating private branch exchanges can be combined with exchanges of a newer type and this type of arrangement is appropriate as a migration solution for a transitional period of time. For the case in which older devices of the type of a switching device 150 are connected, the switching unit MTS is still required in order to perform the connecting function in the area of devices of the type 150. DCL2, as an additional software module, brings the two message paths via DCL and IP2 together and thus covers the existence of two interfaces for the central control ZE2.

35 Figure 5 shows a special embodiment of a private branch  
exchange 450, in which an ATM network is used as the  
second communication connection between the central  
control device. In the case of this special  
configuration of the arrangement, the same ATM network

can be used for the transport network 700 and for the accomplishment of the message traffic via second communication connections by means of the IP protocol. In this case, the transport network 700 and the control  
5 network which is formed by the second communication connections 1020 to 1001 may have a complete different logical structure.

This special embodiment is particularly favorable  
10 because it is possible in this case to dispense with Ethernet connections to the second decentralized devices DZ20 to DZ1 and only a single network infrastructure has to be provided, for example in the form of an ATM network. However, this type of physical  
15 coupling for the accomplishment of the message traffic requires adaptation measures in the area of the central control device ZE2. For this purpose, the central control device ZE2 is divided into two subunits EZE2 and ZZE2, which are connected to each other by a  
20 connecting line Z2020. In this case, the connection to the ATM network is established via the first central unit EZE2, while the message collection evaluation, processing and distribution takes place in the second central device ZZE2. More details on this emerge from  
25 the description of figure 6.

Figure 6 shows a partial view of the private branch exchange 450 which is represented in figure 5. Here, the individual components of the decentralized device  
30 DZ1 and of the first central unit EZE2 and of the second central unit ZZE2 can be seen. Realized in the second decentralized device DZ1, for example by means of a backplane bus, are first communication connections 2015 and 2012, via which a communication of the first  
35 decentralized communication devices DZ15 and DZ12 with a device HDLC1 takes place in accordance with the HDLC protocol.

10088888 "032102

For example, communication terminals are connected to these first decentralized devices. The device HDLC1 serves as a message collecting and distributing device, which terminates the HDLC protocol in the direction of the communication terminals. The messages are passed to the device IP1, which serves for packing the messages into the Internet protocol. HDLC1 and IP1 consequently form the converting device from HDLC to IP. The IP packets are fed to an ATM access device ATM1 and converted there into an ATM cell stream.

The conversion of the data which are transmitted in accordance with the Internet protocol into an ATM cell stream for the device ATM1 may take place either in IPM1 or in ATM1. The data connections I100 and I200 represented are not necessarily lines in the physical sense but functional block interfaces, which may also be formed as software interfaces, for a transfer in the memory for example.

Also represented is an internal connection function IVF, which allows connected terminals access to the transport network 700. These devices are a component part of a decentralized switching device CS1. The message traffic takes place via a second communication connection 1001, which is formed here as an ATM connection. In the first central unit EZE2 there are the same components for a decentralized switching device CS3 as in the case of CS1, although they are marked with the prefix "Z" for differentiation, and they perform the same functions as the components of the same type in the case of CS1. Here, however, a protocol conversion of the Internet protocol via the ATM network to the Internet protocol on the Ethernet takes place. This happens in ZIP or in ZETH. Information between these components is exchanged via an internal connecting line Z100. The Ethernet interface module is linked to the second central unit ZZE2 via the second communication connection 2020 to an

Ethernet access module ETH. By such an arrangement, the ATM access is decoupled from the central control device ZE2. In this way, a second central unit ZZE2 can be constructed in a way essentially similar to a  
5 device ZE2, which was described in figure 2. It is consequently not necessary to carry out elaborate changes in an existing system to enable it to communicate in accordance with the Internet protocol on an ATM network. This property is provided by the first  
10 central unit EZE2. While in the case of known devices the polling of the first decentralized device DZ15 and DZ12 was carried out from the second central unit ZZE2, this now takes place from a representative module HDLC1 in the second decentralized device DZ1.

10088888 032102

199902876

5/pts

## Description

Method and arrangement for coupling messages of a  
central control device with decentralized communication  
5 devices.

The invention relates to a method and an arrangement  
for transporting messages, in particular control  
messages, in a switching device, in particular a  
10 private branch exchange set up over a large area, in  
which a number of decentralized devices are controlled  
from a central device.

The requirements imposed on communication  
15 infrastructure installations, such as private branch  
exchanges for example, are constantly increasing. The  
cause for the increasing requirements with regard to  
the data transmission capacity of switching devices  
lies in the constantly increasing demand for voice,  
20 video and data communication and the consequence that  
networks of broader bands have to be used for  
establishing connections. The cause for greater  
flexibility with regard to the number of subscribers  
which can be connected to switching devices lies in the  
25 requirement for the infrastructure to keep pace  
technically with the flexibility of the business  
processes of the users of the communication device.  
This results in a great demand for flexible modularly  
expandable private branch exchanges.

30

Current devices are based on time-slot multiplexing  
connections between communication terminals which are  
set up by means of a switching unit, for which purpose  
commands which indicate which defined time slot of an  
35 incoming connection is assigned to which defined time  
slot of an outgoing connection are generated by a  
control device. Such switching units are generally  
suitable for the establishment of a defined number of

10088688-032102





demand of a private branch exchange. It is generally in the range of at most several thousand incoming and outgoing connections. Consequently, such devices are not particularly well suited for flexible adaptation to growing numbers of subscribers. Similarly, the data transmission capacity per time slot of a connection is restricted by the ISDN standard (Integrated Services Digital Network) to a maximum of 64 KB. This specified limit hinders, or prevents, a flexible subscriber-specific adaptation of different data rates for each connection.

Moreover, in the case of current devices, the setting-up of a communication infrastructure in the form of a network of decentralized devices which are supplied with messages by a central control is restricted because strict time requirements have to be satisfied when transporting control messages and, as from a defined length of the control line, it is no longer possible to comply with them. Used at present on these message lines is the HDLC protocol (Highlevel Data Link Control), with which messages are transmitted with the function, inter alia, of controlling the access of individual units in the decentralized devices to a PCM data stream (Puls Code Modulation), in that they prescribe defined time slots. If HDLC connections were simply lengthened, the time requirements between the communication partners involved at the end of the link cannot be satisfied. The communication partners would have to be modified in such a way that they impose lower requirements on the time response. This is not practicable, since many possible communication partners are concerned and consequently great expenditure is incurred and the communication partners would have to be provided with more resources, for example memories. The object on which the invention is based is to enter a further method and a further arrangement for coupling



are not subject to any restrictions with regard to the distance between the central device and the decentralized device.

5 This object is achieved for the method in accordance with the features of patent claim 1 and for the arrangement in accordance with the features of patent claim 9. Developments of the invention emerge from the dependent claims.

10

In the case of the method according to the invention, the time-critical message traffic is ensured in a particularly advantageous way by an especially suitable communication protocol on just one partial connection  
15 link. On a further partial connection, in particular a long-distance connection, another, specifically suitable, communication protocol can then be used. This advantageously achieves the effect that already existing modules in decentralized devices can continue  
20 to be used, without the length of the connecting lines to a central control device being subject to restrictions. Similarly, the message transport is advantageously optimized, because the messages are just transported directly and so there is no longer the  
25 additional computational effort which would arise when one protocol is packed into another protocol. Similarly, fewer data therefore have to be transmitted, whereby time advantages and higher data capacities in message transport are attainable.

30

Standardized communication protocols, set up in accordance with the OSI layer model (Open Systems Interconnect), are advantageously used, because  
35 standardized devices (chips, protocol stacks) for such protocols are available on the market, making it easily possible to meet the required increase in the transmission performance on a connection by using faster devices. Since only the messages themselves are

10085553 "03340"

199902876

- 3a -

transmitted on each partial connection link, in an optimum way only the volume of user data is transmitted and the data transmission structures

199902876

can remain restricted to the necessary minimum.

10086688-032102  
5 In the case of a first protocol, the HDLC method is advantageously used on a lowermost layer level, because in this way the modules in the decentralized devices, which today already have an HDLC interface, can continue to be used. This HDLC method is advantageously combined with a second communication protocol, which on the lowermost layers either has an  
10 Ethernet protocol or transmits there in accordance with the ATM protocol. In this way it is possible to use networks that are established and available for long-distance transmission, it being possible as from layer 3 to use the same protocol layers again for the network  
15 switching and transport, in spite of the different fundamentals. For this reason, mixed configurations of a wide variety of protocols and networks can also be set up without any technical development effort. The ATM transmission method is advantageously particularly  
20 suitable for use on a long-distance connection, because different transmission qualities can be set up on the connections, allowing defined time requirements to be met in the message traffic.

25 In a development of the method described, the Internet protocol is advantageously used on the network layer, because this Internet protocol is already available for a wide variety of transmission media, and consequently the same transport and network switching services can  
30 be used for the various transmission media.

35 In a development of the method described, control messages are advantageously transmitted, because in this case there are hard time requirements of the communication partners, according to the method describes no changes are required in the decentralized devices, transmission methods for control messages already exist for the HDLC method,

because they have already been implemented in the case of current devices, and because a wide variety of networks can be used for the long-distance connections.

5 A development of the method described is particularly advantageously suitable for the coupling of a number of decentralized devices to a central control, because messages are collected coordinated and distributed in a decentralized manner and just have to be transmitted in  
10 a bundled manner on a line to the centre.

In the bundling, a number of messages can be advantageously packed into an IP packet and consequently the administrative effort of the protocols can be reduced. The ratio of user data to protocol  
15 data is better as a result, and consequently there is a reduced load on the network.

For the administration of a number of decentralized devices, it is advantageously possible to set up  
20 groups, for which messages are respectively collected and distributed, because in this way message collecting and distributing devices which can already be used for central devices of a known type can be used in decentralized devices.

25 For the case in which a number of groups of decentralized devices are administered, a sorting of the messages is advantageously carried out in the central control device before they are processed,  
30 because in this way a unique group-specific prioritizing and processing of the messages is made possible.

At least two types of connecting lines, on which  
35 different transmission protocols are implemented, are used particularly advantageously in an arrangement for coupling messages between a decentralized device and a central control device. For the exchange of messages

10088888 032100

199902876

- 5a -

in the local exchange area, HDLC-based protocols are advantageously used, because in this way already known

199902876-0340



and existing decentralized devices on the basis of the HDLC protocol with their critical time requirements in decentralized devices can continue to be used, and Internet connections or ATM connections, for which  
5 standardized products are established on the market, can be used for the long-distance connections of these decentralized devices to the central control device, so that, with regard to the transmission capacity, a broad spectrum can be easily covered by the acquisition of  
10 products generally available on the market.

Depending on the required transmission capacity and distance, various media, which are available for the most diverse networks, can be advantageously used for  
15 the long-distance connections. For this reason, in the case of a number of decentralized devices, mixed configurations comprising a wide variety of transmission media are also possible.

20 In a development of the arrangement described, first communication connections advantageously take the form of a backplane bus, because in this way already existing modules can be taken over unchanged from conventional devices into new devices as decentralized  
25 devices. Likewise, this type of configuration requires less additional development effort for the development of decentralized devices.

The protocol conversion takes place particularly  
30 advantageously in the area of a decentralized device, because in this way the time-critical transmission in accordance with the HDLC method can be best ensured. Similarly, there is no need for additional devices which carry out a protocol conversion in the area of  
35 the private branch exchange. Moreover, converting devices arranged decentrally in this way are also able to be adapted exactly in their conversion capacity to the communication volume of the respective

1008855-03340



device, both the information to be transported and the signaling information, exchanged by means of coordinated message traffic, have to be fed to a central device ZE1.

5

To be specific, messages 2, which are to be exchanged between the central device ZE2 and the peripheral devices P1, P2, are collected and distributed by a message device DCL. The setting-up and clearing-down of connections is controlled by means of the Call Processing CP, with the Call Processing using for this purpose, inter alia, device-specific interface functions DH, which are realized for example in the form of program modules. In particular, setting commands 1 for the switching unit MTS are generated. Such a setting command essentially controls which input of the switching unit is to be connected to which output in order to provide a communication connection via this switching device. In such a known communication arrangement, control and connection functions are consequently performed by a single spatially integrated functional unit of the communication network. In the case of such a center-oriented configuration, problems arise because all the data to be transported have to be fed to the central device ZE1. This is the case even if, for example, two communication terminals which are connected to the same peripheral device P1 want to communicate with each other. Such a centrally oriented arrangement also gives rise to high expenditure on cabling, because both the control lines and the communication lines have to be routed to the central device ZE1. It is not possible for peripheral devices to be distributed over a wide area, because the time-critical message traffic via the control lines with the aid of a HDLC protocol cannot take place over links comprising lines of any desired length. To be able to achieve a greater area coverage by means of such devices, the coupling of a



of central interfaces, and for example central facility control, would be lost. Furthermore, when linking them up, additional trunk modules would have to be installed and additional connecting cables would have to be laid  
5 for their connection. Such private branch exchanges also cannot be modularly expanded to whatever extent is desired, because the switching unit MTS for example can only be provided as a complete unit. This means that, in an extreme case, a new switching unit with, for  
10 example, 4096 ports must be purchased and installed for a single additional connection. The transmission rate in such systems is limited for example by the possibility that only a maximum of 64 kbits, or some other administratively fixed or technically dictated  
15 volume of data which is prescribed by the ISDN standard, can be transmitted per time slot. In this case, different data rates for individual communication connections are not possible.

20 Figure 2 shows an example of an arrangement for setting up, clearing down and operating communication connections via decentralized devices which are controlled by a central device. Here, for example, a private branch exchange 250 is represented. The same  
25 component parts of the device are denoted by the same reference numerals in figure 2 as in figure 1. It is notable in the case of this communication arrangement that there are a separate transport network 700 and an independent control network 310/410. Such a setup of  
30 an exchange has the advantage that already existing networks, in the form of public or private networks, can be used for the transport network. What is more, only the control network has to be routed to the central device ZE2.

35

The digital or analog communication terminals KE1 and KE2 are represented in this representation in such a way that they are respectively connected to interface



such terminals which can be connected to the transport network 700 directly, bypassing the interface modules SLMO, are also conceivable and able to be integrated in such an arrangement 250. Consequently, ATM terminals  
5 or IP-based (Internet Protocol) terminals can also be directly connected.

As can also be seen, the decentralized devices DZ1 and DZ2 in each case have decentralized switching devices  
10 CS1 and CS2, which may for example take the form of ATM access devices. Similarly, it can be directly seen that the switching unit MTS0 is no longer used for connection tasks. These connection tasks are instead undertaken by the transport network.

15 For controlling the decentralized switching devices CS1 and CS2, at least one item of control information is in each case transmitted by means of a dedicated message to these switching devices via the control lines 410  
20 and 310, which are component parts of a control network, for setting up and clearing down the communication connection. This control information contains time-slot-related control information, derived from the control instructions for the switching unit  
25 MTS. Furthermore, the figure reveals that a conversion from PCM data into ATM cell data is carried out on a data link 300 or 400. It should be noted here that the use of an ATM network as a transport network serves here merely as an exemplary embodiment. Internet and  
30 other IP connections, or even TDM connections, likewise come into consideration as transport networks. The selection of the respective network is in this case dependent on the intended use and extends over the entire spectrum of available networks, both in the  
35 narrowband range and in the broadband range.

Because the communication connections to the central device ZE2 are no longer needed in such arrangements,

1008858-03240

199902876

- 12a -

in the case of this configuration it is not necessary for connection fees, for instance for both connections from DZ1 and DZ2 to the central device ZE2



For the case in which the second communication connection is formed as an ATM network, the central control device is particularly advantageously divided into two units, of which only one must have an ATM access, while the other may be connected to this unit via a current Ethernet connection. This type of configuration has the advantage that customary central control devices can continue to be used largely unchanged and do not have to be further developed for access to an ATM network. Furthermore, the ATM network can be used for the transmission both of control messages and for the transport of communication data between the terminals, only the Internet protocol having to be implemented on layer 3 of the communication protocol for the transmission of the control messages, and the transfer to the central control device to the Ethernet can also take place on this layer. It is consequently possible to dispense with Ethernet connections between the central control device and the decentralized communication devices. It should be noted here that the network topology for the transport of communication data may well differ from the network topology for the exchange of messages. The user of the communication system has the advantage that he only has to have an ATM network connection, and not also an Ethernet connection.

[illegible]

The message processing takes place particularly advantageously in the second central device, because in this way previously customary peripheral devices can also be involved in the message control sequence, so  
5 that a mixture of previously customary devices of a private branch exchange with novel devices of a new private branch exchange can be operated and controlled in any desired form. In a development of the arrangement described, control messages for the  
10 connection control of a switching unit are generated particularly advantageously in the central control device and transmitted to the second decentralized communication devices, or are used for controlling the switching unit in the case of mixed arrangements. In  
15 this way, connections can be established in the entire area of the switching device, irrespective of whether the communication subscribers are connected to novel devices or to customary devices.

20 Exemplary embodiments of the invention are explained in more detail below on the basis of figures:

- figure 1 shows a conventional communication arrangement,  
25 figure 2 shows an example of a communication arrangement with decentralized devices,  
figure 3 shows a network structure comprising a central device and a number of decentralized devices,  
30 figure 4 illustrates the linking of a decentralized device to a central device,  
figure 5 illustrates an advantageous configuration of an arrangement for coupling messages on the basis of an ATM network,  
35 figure 6 shows a view of a detail of the coupling of decentralized devices to a central control device via an ATM network.

Figure 1 shows an example of a known private branch exchange 150 with a central control device. This private branch exchange is connected to two peripheral devices P1 and P2, to which there is respectively  
5 connected a communication terminal KE1 and KE2 operating on a digital or analog basis. These peripheral devices P1 and P2 are accommodated in the same spatial area as the first central device Z1. They are consequently located in the same space or in the  
10 same cabinet as it. The terminals occupy defined time slots of a PCM data stream (Puls Code Modulation) with communication data. In this case, these analog or digital communication terminals KE1 and KE2 are connected via interface modules SLM01 and SLM02, which  
15 feed to the PCM data stream, or remove from it, data which are intended for the respective terminals, or come from the respective terminals, via time slots established by control messages. Two PCM data streams are denoted in the figure by 100 and 200, respectively.  
20 Likewise represented are signaling connections 110 and 210, via which message traffic with a central control can take place. In the case of this representation it should be noted that only a logical representation of the connections is shown in the topology for individual  
25 connections, and that this is not a physical representation. In the technical realization of these networks, the transport data and the messages can be transmitted over the same connection medium without restriction.  
30  
Also represented are peripheral devices P1 and P2, and also the supply modules LTUC1 and LTUC2, which regulate the data traffic to the interface modules, for example SLM01 and SLM02, of the respective peripheral devices.  
35 In this case, the peripheral device is fed control messages via the line 110 and the peripheral device P2 is fed control messages via the line 210. It can be clearly seen in the case of this known private branch

10086666.032102



via public lines, for example fixed lines, to be paid, as previously the case with a remote peripheral device PE in a device 150 from figure 1 when there is communication from PE1 to PE2. For controlling the setting-up of the connection and the associated exchange of messages, a transport-network-dependent call processing is carried out on the decentralized switching devices CS1 and CS2, but is restricted essentially to basic call functionality. The facilities are in this case realized and provided by the central control ZE2. Connections between the various central devices are controlled by the central devices ZE2 by means of messages which contain control information.

The advantages of such an arrangement are that it is capable of both narrowband and broadband operation. A possibly used backplane in the decentralized device would have to be newly developed, however, in order to allow broadband connections to be established, in contrast to TDM backplanes. Furthermore, the transport network can be set up both on public networks and on private networks, or else on a mixture of the two. Furthermore, there is the possibility of assigning to the central device ZE2 decentralized devices that are an unlimited distance away, so that even very large installations can be provided with such a private branch exchange, which in turn serve for supplying widespread areas with communication connections. In this case, because a central device is retained, there is the possibility of continuing to use already existing software, with minimal changes, for the control. On the other hand, new methods of control would have to be developed and a new mechanism for ensuring consistency of a distributed database would have to be created if the control, like the switching unit, were likewise distributed. A further advantage

199902876

- 13a -

of such a device 250 in comparison with networked  
systems of the type

10088638-03210

5

15

35





of a second decentralized device for any number of such first decentralized devices to be connected to the latter via respective first communication connections. Furthermore, connected to the second decentralized device DZ10 are first decentralized devices DZ102, ZD105 and DZ108 via first communication connections 2102, 2105 and 2108. The functionality of the second decentralized devices for the message traffic is essentially identical. For the exchange of messages with the central control device ZE2, first decentralized devices DZ202, DZ207 and DZ237 are connected to the second decentralized device DZ20 via first communication connections 2202, 22207 and 2237. In a favorable configuration of an arrangement, the first decentralized devices DZ12 to DZ 237 are configured as interface modules for communication terminals SLMO. The first communication connections 2012 to 2237 to the respective first decentralized devices are generally connections via which time-critical control messages are transmitted. For this purpose, the HDLC method is used between the first decentralized device and the second decentralized device as the first communication protocol. These first communication connections may advantageously take the form of a backplane bus of a second decentralized device. This variant of the configuration allows modules which are used in conventional systems for the connection of communication terminals to be used as first decentralized devices.

The second decentralized communication devices are connected over relatively great distances, via LANs (Local Area Networks) or WANs (Wide Area Networks) such as Ethernet or ATM connections for example, to the central control device ZE2. On these second communication connections, a layer protocol of the ISO type (Open Systems Interconnect) of protocol is



layer the link layer, the third the network layer, the fourth the transport layer, the fifth the session control, the sixth the data presentation and the seventh the application layer. In this layer protocol, standardized in accordance with ISO IS8802, each layer uses the services of the layer lying under it. Messages which are transmitted with the aid of this layer protocol consequently receive additional information successively at each layer, thus producing a data structure in which the original message has seven layer-specific elements of information added to it. This process is also known as "packing" the information, whereas the reverse process, in which the corresponding elements of the structure are returned layer-dependently to the respective layers to produce the original message, is known as "unpacking". Theoretically, the possibility of interleaving a number of such protocols would also exist, but would necessitate a considerable administrative effort and would lead to increased loading of the second communication connection during the data transmission, because the information on the layer organization of the other protocol has to be additionally transmitted along with the actual message itself.

For converting the HDLC protocol used on the first communication connection into the OSI protocol layers used on the second communication connection, for example in the form of the layer sequences Ethernet/IP/TCP or ATM/IP/TCP, there is in a respective second decentralized device DZ1 to DZ20 in each case a device for protocol transformation of the messages to be exchanged, this device in each case performing the conversion by unpacking the message completely from the protocol used and then packing it into the other protocol and passing it on. As the figure further reveals, various first decentralized devices and second decentralized devices form groups. These groups are

devices which are spatially close together and may, for example,

Previously customary peripheral devices are also linked to ZE2 via a device DCL (not represented). An additional software module decides whether messages are sent as before via DCL or via the IP path and consequently via the Ethernet connection. In the opposite direction, this software similarly forms both inputs (DCL and IP) in one. Consequently, the additional software module provides a uniform interface in the direction of the system software and covers the split into two different paths and types of transmission.

In connection with the reference numerals which are used in the various figures, it must also be noted that the same reference numerals also concern communication devices or component parts of communication arrangements of the same type. The second communication connections to the central control device may be configured on a wide variety of communication media, it being possible for the Internet protocol to be used on layer 3 and the Transmission Control Protocol TCP to be used on layer 4. Various mixed variants are conceivable here. This protocol structure achieves the effect that, as from layer 3, messages can be exchanged over a wide variety of communication media system-wide.



device is in connection with a message processing and control device DCL2, which in the case of the central control device ZE2 possibly prioritizes, sorts, passes on for processing or sends messages also arriving from peripheral devices via DCL, or sent from it.

As can be further seen, in the arrangement represented the switching unit MTS no longer performs any function. However, it is conceivable that a peripheral device, which is represented in figure 1, is connected to ZE2 via a decentralized switching device of the same type as CS1, the message traffic with ZE2 continuing to be handled by means of HDLC via DCL and DCL2. In this way, conventional, already operating private branch exchanges can be combined with exchanges of a newer type and this type of arrangement is appropriate as a migration solution for a transitional period of time. For the case in which older devices of the type of a switching device 150 are connected, the switching unit MTS is still required in order to perform the connecting function in the area of devices of the type 150.

DCL2, as an additional software module, brings the two message paths via DCL and IP2 together and thus covers the existence of two interfaces for the central control ZE2.

Figure 5 shows a special embodiment of a private branch exchange 450, in which an ATM network is used as the second communication connection between the central control device. In the case of this special configuration of the arrangement, the same ATM network can be used for the transport network 700 and for the accomplishment of the message traffic via second communication connections by means of the IP protocol. In this case, the transport network 700 and the control network which is formed by the second communication

199902876

- 19a -

connections 1020 to 1001 may have a complete different logical structure.



1008555-032102

This special embodiment is particularly favorable because it is possible in this case to dispense with Ethernet connections to the second decentralized devices DZ20 to DZ1 and only a single network 5 infrastructure has to be provided, for example in the form of an ATM network. However, this type of physical coupling for the accomplishment of the message traffic requires adaptation measures in the area of the central control device ZE2. For this purpose, the central 10 control device ZE2 is divided into two subunits EZE2 and ZZE2, which are connected to each other by a connecting line Z2020. In this case, the connection to the ATM network is established via the first central unit EZE2, while the message collection evaluation, 15 processing and distribution takes place in the second central device ZZE2. More details on this emerge from the description of figure 6.

Figure 6 shows a partial view of the private branch 20 exchange 450 which is represented in figure 5. Here, the individual components of the decentralized device DZ1 and of the first central unit EZE2 and of the second central unit ZZE2 can be seen. Realized in the second decentralized device DZ1, for example by means 25 of a backplane bus, are first communication connections 2015 and 2012, via which a communication of the first decentralized communication devices DZ15 and DZ12 with a device HDLC1 takes place in accordance with the HDLC protocol.

30 For example, communication terminals are connected to these first decentralized devices. The device HDLC1 serves as a message collecting and distributing device, which terminates the HDLC protocol in the direction of 35 the communication terminals. The messages are passed to the device IP1, which serves for packing the messages into the Internet protocol. HDLC1 and IP1 consequently form the converting device from HDLC to



The conversion of the data which are transmitted in accordance with the Internet protocol into an ATM cell stream for the device ATM1 may take place either in IPM1 or in ATM1. The data connections I100 and I200  
5 represented are not necessarily lines in the physical sense but functional block interfaces, which may also be formed as software interfaces, for a transfer in the memory for example.

Also represented is an internal connection function  
10 IVF, which allows connected terminals access to the transport network 700. All these devices are a component part of a decentralized switching device CS1. The message traffic takes place via a second communication connection 1001, which is formed here as  
15 an ATM connection. In the first central unit EZE2 there are the same components for a decentralized switching device CS3 as in the case of CS1, although they are marked with the prefix "Z" for differentiation, and they perform the same functions as  
20 the components of the same type in the case of CS1. Here, however, a protocol conversion of the Internet protocol via the ATM network to the Internet protocol on the Ethernet takes place. This happens in ZIP or in ZETH. Information between these components is  
25 exchanged via an internal connecting line Z100. The Ethernet interface module is linked to the second central unit ZZE2 via the second communication connection 2020 to an Ethernet access module ETH. By such an arrangement, the ATM access is decoupled from  
30 the central control device ZE2. In this way, a second central unit ZZE2 can be constructed in a way essentially similar to a device ZE2, which was described in figure 2. It is consequently not necessary to carry out elaborate changes in an existing  
35 system to enable it to communicate in accordance with the Internet protocol on an ATM network. This property is provided by the first central unit EZE2. While in the case of known devices the polling of the first

1008553 "03210"





## Patent claims

1. A method for coupling messages of a central control device with decentralized communication devices having the following features:
- a) message traffic takes place on at least two partial connection links (KV1, 1001);
  - b) different communication protocols are used on the partial connection links;
  - c) a respective message is transmitted on the partial connection link directly as such with the respective communication protocol.
2. The method as claimed in claim 1, in which, for the transformation from one type of communication protocol into another type of communication protocol, the message is initially unpacked from the protocol layers of one protocol and then packed into the protocol layers of the other protocol.
3. The method as claimed in one of the preceding claims, in which the HDLC method is used in the case of a first communication protocol on a lower protocol layer level and the Ethernet protocol or the ATM protocol is used in the case of a second communication protocol on a lower layer.
4. The method as claimed in claim 2 or 3, in which the Internet protocol is used on a network protocol layer.
5. The method as claimed in one of the preceding claims, in which a control message is transmitted.
6. The method as claimed in one of the preceding claims, in which, for the case in which messages take place from a number of first decentralized devices (DZ12, ..., DZ237), these are transmitted

after passing through a first partial connection link (2012,..., 2237) in a second decentralized device (DZ1,...,DZ20) in a bundled form and on only one second partial connection link (1001,...,1020).

5

7. The method as claimed in claim 6, in which groups of a number of first decentralized devices (DZ12, DZ15, DZ19) and second decentralized devices (DZ1) are administered.

10

8. The method as claimed in claim 7, in which the messages from/to the second decentralized devices (DZ1,..., DZ10, DZ20) are initially sorted and then processed in the central control device (ZE2).

15

9. An arrangement for coupling messages of a central control device with decentralized communication devices,

20

a) with at least one first decentralized communication device (DZ12,...,DZ237) for receiving and/or issuing a message,

b) with at least one second decentralized communication device (DZ1,...,DZ20) for collecting and/or distributing messages,

25

c) with a central control device (ZE2) for issuing and receiving messages,

d) with at least one first communication connection (2012,...,2237) between the first and second communication devices,

30

e) with a second communication connection (1001,...,1020) between the second decentralized communication device (DZ1,...,DZ20) and the central control device (ZE2), the second communication connection being formed as an Internet or ATM network, and the first communication connection being formed as an HDLC-based connection.

35

10. The arrangement as claimed in claim 9, in which the second communication connection (1001,...,1020) is formed as a coaxial cable or as an optical waveguide.



11. The arrangement as claimed in one of claims 9 or 10, in which the first communication connection (2012,...,2237) is formed as a bus on a backplane.
12. The arrangement as claimed in one of claims 9 to 11, in which the second decentralized communication device (DZ1,...,DZ20) is in operative connection with a converting device (HDLCL1, IP1), which performs a protocol conversion between communication protocols on the first and second communication connections, for which purpose the messages are completely unpacked from protocol layers being used and re-packed.
13. The arrangement as claimed in one of claims 9 to 12, in which, for the case in which a number of second communication devices (DZ1,...,DZ20) are connected via a number of second communication connections (1001,...,1020) to the central control device (ZE2), there is at least one device there for coordination of the messages (IP2, DCL2), which sorts [lacuna] arriving on the second communication connection or on the way there, which is connected to a device for processing the messages (DCL2).
14. The arrangement as claimed in one of claims 9 to 13, in which, for the case in which the second communication connection (1020,...,1001) is formed as an ATM network, the central control device (ZE2) has a first and a second central device (EZE2, ZZE2), a converting device (ZIP) being present in the first central device (EZE2), for the conversion between protocol layers of the Internet protocol via the ATM network to protocol layers of the Internet protocol via the Ethernet (ZETH), and in which the first and second central devices (EZE2, ZZE2) are in connection with each other via an Ethernet connection (Z2020).

15. The arrangement as claimed in claim 14, in which the second central device (ZZE2) has the device for processing messages (DCL2).
- 5 16. The arrangement as claimed in one of claims 14 to 15, in which the central control (ZE2) has means for controlling a switching unit for the creation of time-slot multiplex connections, and these means are in operative connection with the means for
- 10 processing messages (DCL2).

5

10

(12) NACH DEM VERTRAG ÜBER DIE INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES  
PATENTWESENS (PCT) VERÖFFENTLICHTE INTERNATIONALE ANMELDUNG

(19) Weltorganisation für geistiges Eigentum  
Internationales Büro



(43) Internationales Veröffentlichungsdatum  
29. März 2001 (29.03.2001)

PCT

(10) Internationale Veröffentlichungsnummer  
WO 01/22677 A2

(51) Internationale Patentklassifikation: H04L 29/00

(21) Internationales Aktenzeichen: PCT/DE00/03175

(22) Internationales Anmeldedatum:  
13. September 2000 (13.09.2000)

(25) Einreichungssprache: Deutsch

(26) Veröffentlichungssprache: Deutsch

(30) Angaben zur Priorität:  
199 45 152.4 21. September 1999 (21.09.1999) DE

(71) Anmelder (für alle Bestimmungsstaaten mit Ausnahme von  
US): SIEMENS AKTIENGESELLSCHAFT [DE/DE];  
Wittelsbacherplatz 2, D-80333 München (DE).

(72) Erfinder; und

(75) Erfinder/Anmelder (nur für US): WINDECKER,  
Rainer [DE/DE]; Gustav-Heinemann-Ring 94, D-81739  
München (DE). WINKLER, Steffi, Lissi [DE/DE];  
Lulu-Beck-Weg 13, D-82131 Gauting (DE). KLEIN,  
Egon, Franz [DE/DE]; Münchener Str. 14, D-82110  
Germering (DE). EMMERINK, Antonius [NL/DE];  
Ayingenstr. 4, D-84671 München (DE). STEFFAN, An-  
dreas [DE/DE]; Sentlostr. 43, D-81477 München (DE).


(74) Gemeinsamer Vertreter: SIEMENS AKTIENGE-  
SELLSCHAFT; Postfach 22 16 34, D-80506 München  
(DE).

(81) Bestimmungsstaaten (national): CA, CN, JP, US.

[Fortsetzung auf der nächsten Seite]

(54) Title: METHOD AND ARRANGEMENT FOR COUPLING MESSAGES IN A CENTRAL CONTROL DEVICE WITH DE-  
CENTRALISED COMMUNICATIONS DEVICES

(54) Bezeichnung: VERFAHREN UND ANORDNUNG ZUR MELDUNGSKOPPLUNG EINER ZENTRALEN STEUERUNGS-  
EINRICHTUNG MIT DEZENTRALEN KOMMUNIKATIONSEINRICHTUNGEN



(57) Abstract: The invention relates to a novel private extension unit arrangement and the migration solutions of existing devices. Communications links are produced by means of a transport network. Control is carried out in a centralised manner by means of a central control device which is connected to the decentralised network devices and the interface modules via a two-step connection. The control messages are collected and distributed in a decentralised manner. The control connection from a decentralised device respectively to the central control device is provided via an ATM network or an ethernet connection.

[Fortsetzung auf der nächsten Seite]

WO 01/22677 A2

WO 01/22677 A2






FIG 3




FIG 5




FIG 4





FIG 6





## IDNR: 2590 / V: 99-1.00 / B:Val

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

### Method and arrangement for coupling messages in a central control device with decentralised communications devices

the specification of which

(check one)

☐ is attached hereto.

☒ was filed on 13.09.2000 as

PCT international application

PCT Application No. PCT/DE00/03175

and was amended on \_\_\_\_\_

(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

[illegible]

Priority Claimed

☐ No

Yes

No

FORMTEXT

☐ Yes

Ja

☐ No

Nein

☐ Yes

Ja

☐ No

Nein

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §122, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

pending  
(Status)  
(patented, pending,  
abandoned)

(Status)  
(patented, pending,  
abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

## German Language Declaration

VERTRETUNGSVOLLMACHT: Als benannter Erfinder beauftrage ich hiermit den nachstehend benannten Patentanwalt (oder die nachstehend benannten Patentanwälte) und/oder Patent-Agenten mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Geschäfte vor dem Patent- und Warenzeichenamt: (Name und Registrationsnummer anführen)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Customer No. 25227

And I hereby appoint

Telefongespräche bitte richten an:  
(Name und Telefonnummer)

Direct Telephone Calls to: (name and telephone number)

Ext. \_\_\_\_\_

Postanschrift:

Send Correspondence to:

Morrison and Foerster LLP  
2000 Pennsylvania Ave., NW 20006-1888 Washington, DC  
Telephone: (001) 202 887 1500 and Facsimile (001) 202 887 0763

or

Customer No. 25227

Voller Name des einzigen oder ursprünglichen Erfinders:		Full name of sole or first inventor:	
Antonius Emmerink		Antonius Emmerink	
Unterschrift des Erfinders	Datum	Inventor's signature	Date
<i>[Signature]</i>	25.2.2002		
Wohnsitz		Residence	
Muenchen, DEUTSCHLAND (DE)		Muenchen, GERMANY	
Staatsangehörigkeit		Citizenship	
NL		NL	
Postanschrift		Post Office Address	
Ayingerstrasse 4		Ayingerstrasse 4	
81671 Muenchen		81671 Muenchen	
Voller Name des zweiten Miterfinders (falls zutreffend):		Full name of second joint inventor, if any:	
Egon Klein		Egon Klein	
Unterschrift des Erfinders	Datum	Second Inventor's signature	Date
<i>[Signature]</i>	22.2.2002		
Wohnsitz		Residence	
Germering, DEUTSCHLAND (DE)		Germering, GERMANY	
Staatsangehörigkeit		Citizenship	
DE		DE	
Postanschrift		Post Office Address	
Muenchener Str. 14		Muenchener Str. 14	
82110 Germering		82110 Germering	

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).

10088888 032102

Voller Name des dritten Miterfinders: <b>Andreas Steffan</b>		Full name of third joint inventor: <b>Andreas Steffan</b>	
Unterschrift des Erfinders <i>A. Steffan</i>	Datum <b>25.02.02</b>	Inventor's signature	Date
Wohnsitz <b>Muenchen, DEUTSCHLAND (DE)</b>		Residence <b>Muenchen, GERMANY</b>	
Staatsangehörigkeit <b>DE</b>		Citizenship <b>DE</b>	
Postanschrift <b>Sentilostr. 43</b>		Post Office Address <b>Sentilostr. 43</b>	
<b>81477 Muenchen</b>		<b>81477 Muenchen</b>	
Voller Name des vierten Miterfinders: <b>Rainer Windecker</b>		Full name of fourth joint inventor: <b>Rainer Windecker</b>	
Unterschrift des Erfinders <i>Rainer Windecker</i>	Datum <b>04.03.2002</b>	Inventor's signature	Date
Wohnsitz <b>Muenchen, DEUTSCHLAND (DE)</b>		Residence <b>Muenchen, GERMANY</b>	
Staatsangehörigkeit <b>DE</b>		Citizenship <b>DE</b>	
Postanschrift <b>Gustav-Heinemann-Ring 94</b>		Post Office Address <b>Gustav-Heinemann-Ring 94</b>	
<b>81739 Muenchen</b>		<b>81739 Muenchen</b>	
Voller Name des fünften Miterfinders: <b>Steffi Winkler</b>		Full name of fifth joint inventor: <b>Steffi Winkler</b>	
Unterschrift des Erfinders <i>Steffi Winkler</i>	Datum <b>27.2.02</b>	Inventor's signature	Date
Wohnsitz <b>Gauting, DEUTSCHLAND (DE)</b>		Residence <b>Gauting, GERMANY</b>	
Staatsangehörigkeit <b>DE</b>		Citizenship <b>DE</b>	
Postanschrift <b>Lulu-Beck-Weg 13</b>		Post Office Address <b>Lulu-Beck-Weg 13</b>	
<b>82131 Gauting</b>		<b>82131 Gauting</b>	
Voller Name des sechsten Miterfinders:		Full name of sixth joint inventor:	
Unterschrift des Erfinders	Datum	Inventor's signature	Date
Wohnsitz		Residence	
Staatsangehörigkeit		Citizenship	
Postanschrift		Post Office Address	

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).